

U.S. G.S. FORM 100-101  
MAY 1970

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Form approved  
Bureau of Land Management  
Circular Bulletin No. 42 R1421

5. LEASE DESIGNATION AND SERIAL NO.

NM-28306

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Use this form for proposals to drill or re-drill, or plug back to a different reservoir.  
Use APPLICATION FOR PERMIT for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR  
McClellan Oil Corporation

3. ADDRESS OF OPERATOR  
Post Office Drawer 730, Roswell, New Mexico 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

1650' FSL & 660' FWL

RECEIVED

APR 10 1981

O. C. D.  
ARTESIA, OFFICE

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Coyote Draw Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 6-T8S-R25E

12. COUNTY OR PARISH

Chaves

13. STATE

NM

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3776 G.L.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Casing Report

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

2/24/81: Drilled to 80' and ran 80' of 20" casing in 24" hole. Cemented with 8 yards of Redi-Mix.

3/17/81: Moved in Tex-Mex Rig #2.

3/19/81: Spudded with 17½" bit.

3/21/81: Drilled to 450' with 17½" bit. Ran 451' of 13-3/8" J-55, 54.5 lb/ft casing. Cemented with 200 sacks Halliburton Light Cement with 2% CaCl<sub>2</sub> and 200 sacks Class "C" cement with 2% CaCl<sub>2</sub>. Circulated 50 sacks. WOC 12 hours.

18. I hereby certify that the foregoing is true and correct

SIGNED

(This space for Federal

APPROVED BY

CONDITIONS OF APPROVAL IF ANY

ACCEPTED FOR RECORD

PETER W. CHESTER

APR 8 1981

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

TITLE Engineer

TITLE

DATE 3/24/81

DATE

See Instructions on Reverse Side