

NMOOD COPY

Form 9-331
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 27970

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

RECEIVED

7. UNIT AGREEMENT NAME

APR 06 1981

8. FARM OR LEASE NAME

COYOTE FEDERAL O. C. D.

9. WELL NO.

ARTESIA OFFICE

5

10. FIELD AND POOL, OR WILDCAT

UNDESIGNATED ABO

11. SEC., T., R., M., OR BLE. AND
SURVEY OR AREA

SEC 19, T7S, R25E

12. COUNTY OR PARISH
CHAVES

13. STATE
NEW MEXICO

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL ☐ GAS ☒ OTHER ☐
WELL WELL

2. NAME OF OPERATOR

Mesa Petroleum Co. /

3. ADDRESS OF OPERATOR

1000 Vaughn Building / Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)
See also space 17 below.)

At surface 1980' FNL & 660' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3850.7' GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) 8 5/8" CSG & CEMENT

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

X

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 11" hole to 1603' on 3-23-81. NOTE: Hit 150 BPH salt water at 1275'.
Ran 35 jts 8 5/8", 24#, J-55 casing set at 1598'. Cemented with 350 sx LT +
4% CaCl, 400 sx Thixset + 4% CaCl, 350 sx LT + 4% CaCl, and tailed in with
200 sx "C" + 2% CaCl. PD at 2:30 PM 3-23-81. Cement circulated. WOC 10 hours,
tested BOP's & casing to 600 psi for 30 min - OK. Reduced hole to 7 7/8" and drilled
ahead on 3-24-81.

XC: USGS (3), TLS, ROSWELL, MEC, PARTNERS, FILE

18. I hereby certify that the foregoing is true and correct

SIGNED PETER W. CHESTER ACCEPTED FOR RECORD

TITLE REGULATORY COORDINATOR

DATE MARCH 27, 1981

(This space for Federal or State office use)

APPROVED BY APR 3 1981
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

Instructions on Reverse Side