

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐ MAR 03 1981

2. NAME OF OPERATOR
MESA PETROLEUM CO.

3. ADDRESS OF OPERATOR
1000 VAUGHN BUILDING/MIDLAND, TEXAS 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980' FSL & 660' FEL

14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3585.3' GR

5. LEASE DESIGNATION AND SERIAL NO.

NM 14987

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

GARCIA FEDERAL

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

WILDCAT

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

SEC 11, T8S, R24E

12. COUNTY OR PARISH

CHAVES

13. STATE

NEW MEXICO

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) 8 5/8" CSG & CEMENT

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 11" hole to 1835' 2-19-81, ran 41 jts 8 5/8", 24#, J-55 csg set at 1820'. Cemented with 350 sx Lt & 4% CaCl, 200sx Thixset & 4% CaCl 350 sx Lt & 4% CaCl, 200 sx Thixset & 4% CaCl, 350 sx Lt & 4% CaCl and tailed in with 300 sxs "C" + 2% CaCl. PD at 10:15 AM 2-19-81. Cement did not circulate. Dumped 2 1/2 yds gravel & 50 sx Thixset + 4% CaCl, to raise cement to surface. WOC total of 10 1/2 hours. Tested BOP's and casing to 600 psi for 30 mins - OK. Reduced hole to 7 7/8" and drilled ahead on 2-20-81.

XC: USGS (6), TLS, HOBBS, MEC, LAND, FILE

18. I hereby certify that the foregoing is true and correct

SIGNED

R. E. [Signature]

TITLE

REGULATORY COORDINATOR

DATE FEBRUARY 24, 1981

(This space for Federal or State Use Only)

APPROVED BY

CONDITIONS OF APPROVAL IF ANY:

ACCEPTED FOR RECORD
PETER W. CHESTER

FEB 27 1981

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

See Instructions on Reverse Side