

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

| | |
|------------------------|-------------------------------------|
| NO. OF COPIES RECEIVED | |
| DISTRIBUTION | |
| SANTA FE | <input checked="" type="checkbox"/> |
| FILE | <input checked="" type="checkbox"/> |
| U.S.G.S. | |
| LAND OFFICE | |
| OPERATOR | <input checked="" type="checkbox"/> |

5a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.
L5250

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

RECEIVED

OIL WELL ☐ GAS WELL ☒ OTHER- New Well

AUG 07 1981

Name of Operator
Energy Resources Oil & Gas Corporation /

7. Unit Agreement Name

8. Farm or Lease Name
State 4A

Address of Operator
2735 Villa Creek Dr., Suite 165, Dallas, TX 75234

9. Well No.
1

Location of Well

UNIT LETTER L 660 FEET FROM THE West LINE AND 1980 FEET FROM

10. Field and Pool, or Wildcat
Wildcat-Montoya

THE South LINE, SECTION 4 TOWNSHIP 5S RANGE 26E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)
3809.8 G.L.

12. County
Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

REMEDIATION WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☒
OTHER ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Operator has plugged and abandoned the subject well as follows:

1. Set 25 sxs Class "C" cement + 3% CaCl plug across perfs at 1598'-1608'. Plug coverage from 1704' up to 1394' (310').
2. Cut off 4-1/2" casing at 1307' - pulled same.
3. Set 35 sxs Class "C" cement + 3% CaCl plug on top of 4-1/2" casing stub from 1355' to 1225' (130').
4. Set 15 sxs Class "C" cement + 3% CaCl plug on top and inside surface casing. Cemented 4" x 8' regulation I.D. marker 4' above ground level. Location and pits to be cleared and leveled as conditions permit.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Robert Becerra

TITLE Oper. mgr

DATE 7-24-81

APPROVED BY Darrell Moore

TITLE Geologist

DATE 1/2/86

ADDITIONS OF APPROVAL, IF ANY: