

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND

(Do not use this form for proposals to drill a well or to plug back to a different reservoir. Use Form 9-331-C for such purposes.)

1. oil well ☐ gas well ☒ other ☐

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th St., Ar

4. LOCATION OF WELL (REPORT below.)

AT SURFACE: 660' FWL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX  
REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) ☐

17. DESCRIBE PROPOSED OR CURRENT OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of start and completion, and true vertical depth measured and true vertical depth of well.)

Spudded a 17-1/2" hole at TD 390'. Ran 10 joints 13-Class C 4% CaCl. Slurry plug to 900 psi, released 2840 psi in 12 hours. Circulated 40 sacks to surface. WOC 12 hours. TD 1330'. Ran 33 joints of pattern guide shoe at 133 sacks 65-35 Poz, 4% Bento in w/150 sacks Class C 2% released pressure & float strength of cement - 500 to 1500 psi, okay. Reduced

Subsurface Safety Valve: Manual

18. I hereby certify that the foregoing is true and correct.

SIGNED \_\_\_\_\_

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

REPORTS ON WELLS

(Do not use this form for proposals to drill a well or to plug back to a different reservoir. Use Form 9-331-C for such purposes.)

on

a, NM 88210

LOCATION CLEARLY. See space 17

60' FEL

19. INDICATE NATURE OF NOTICE,

SUBSEQUENT REPORT OF:

☒  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

20. DESCRIBE PROPOSED OR CURRENT OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of start and completion, and true vertical depth measured and true vertical depth of well.)

10 PM 2-9-81

48# H-40 casing set at 390'. Cemented w/400 sacks light 14.8, 1.32 cu/ft sack. PD 7:00 AM 2-10-81. Bumped pressure & float held okay. Compressive strength of cement - 40 sacks to surface. WOC 12 hours. 7/8" 24# ST&C K-55 casing set at 1330'. 1-regular Flapper insert float at 1290'. Cemented w/400 sacks, 8# Kolite, 1/4# celloflakes & 3% CaCl. Tailed 11. PD 4:30 PM 2-13-81. Bumped plug to 900 psi, held okay. Circulated 50 sacks to pit. Compressive strength of cement - 500 to 1500 psi, okay. Reduced hole to 7-7/8". Drilled plug & resumed drilling.

Set @ \_\_\_\_\_ Ft.

Engineering Secretary

TITLE \_\_\_\_\_ DATE 2-18-81

(This space for Federal or State office use)

TITLE \_\_\_\_\_

ACCEPTED FOR RECORD

DATE

FEB 20 1981

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

\*See Instructions on Reverse Side

APPROVED FOR RELEASE  
FEB 20 1981  
U.S. DEPARTMENT OF JUSTICE  
FEDERAL BUREAU OF INVESTIGATION