	NM OIL CONS. COMMI Drawer DD	2210N
Form 9–331 *AM	D REPORTArtesia, NM 88210	rom npproved.
U	D STATES	Budget Bureau No. 42-R1424 5. LEASE
DEPARTM	OF THE INTERIOR	NM - 2351
GEO	ICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES	ND REPORTS ON WELLS	7. UNIT AGREEMENT NAME - RECEIVED
(Do not use this form for propos reservoir. Use Form 9–331–C for	drill or to deepen or plug back to a different roposals.	8. FARM OR LEASE NAME HILL TO HOO
1. oil XI gas	-	8. FARM OR LEASE NAME JUL 9 198
well well well	.her	9. WELL NO.
NAME OF OPERATOR Yates Petrole	orporation	3 ADSESSA CASSOE
3. ADDRESS OF OPERATO		Wildcat / A /
207 South 4th	, Artesia, NM 88210	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (R below.)	IT LOCATION CLEARLY. See space 17	AREA Unit A, Sec. 34-7S-25E
AT SURFACE: 660' AT TOP PROD. INTERN	& 760' FEL	12. COUNTY OR PARISH 13. STATE Chaves NM
AT TOTAL DEPTH:	1951 F	14. API NO.
16. CHECK APPROPRIATE REPORT, OR OTHER D	TO INDICATE NATURE OF NOTICE,	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL	SUBSEQUENT REPORT OF:	3633.8' GR
TEST WATER SHUT-OFF		
FRACTURE TREAT SHOOT OR ACIDIZE		
REPAIR WELL		ONOTE HARE RESIDENT TO THE ESTIMATION OF ZONE
PULL OR ALTER CASING MULTIPLE COMPLETE	[X]	The second secon
CHANGE ZONES	\mathbf{x}	JUL 0 1 1981
ABANDON* (other)		OIL & GAS
		U.S. GEOLOGICAL SURVEY
 DESCRIBE PROPOSED including estimated dat measured and true verti 	OMPLETED OPERATIONS (Clearly stat starting any proposed work. If well is dapths for all markers and zones pertiner	e all pertinent details, and give pertinent dates
$\frac{\text{TD } 4450'}{(-1)^{2}}$ TOOH w/2-3	tubing. Set CIBP at 3700' w/35' of cement on top. Cut	
4-1/2" casing off at Circulated hole w/ge	27'. Laid down 63 jts & stub of 4-1/2" 9.5# casing.	
stub from 2475-2575'	ater. *Spotted 20 sacks Class "C" plug across 4-1/2" Spotted 40 sacks Class "C" plug across bottom 8-5/8"	
casing from 1280-138	Tested plug across 8-5/8" shoe to 2000 psi okay.	
Spotted 3 bbls acid.	<pre>[H w/Steel strip gun & per:</pre>	forated 11 .50" holes from
869-77 & 885-88'. A	ized w/1500 gallons 15% DS-	-30, plus 15 ball sealers.
Subsurface Safety Valve: Ma	nd Type	Set @
18. I hereby certify that the	Ding is true and correct	350 @ 1.1.1
SIGNED/Li aneta		ecty date 6/30/81
		······································
ACCEPTE ROGER	R RECORDNIS space for Federal or State off HAPMAN	ice use)
CONDITIONS OF APPROVAL, IF	TITLE	DATE

l 1981

CAL SURVEY Instructions on Reverse Side

JIJL

U.S. GEOL