STATE OF NEW MEXICO

work) SEE RULE 1103.

ENERGY AND MINERALS DEP	AMINIEN - (L CONSERVAT	TION DIV	15101		
		P. O. BOX	2088	RECEIVED	Form C-1 Revised	
DISTRIBUTION	, ,	SANTA FE, NEW	MEXICO 87	501		
SANTA PE	\ 	3AN 1 A 1 A 1 A 1 A 1 A 1 A 1 A 1 A 1 A 1			5a, Indicate Type of Lease	
71LE V.S.Q.S.	- - 			APR 1 4 1981		• X
LAND OFFICE					5. State Oil 6 Gas Lease No.	
OPERATOR				O. C. D.	3, 51dit Oil & Cas 21 and 1	
				ARTESIA, OFFICE	THITTING TO SEE	7777
LOO HOT USE THIS FORM	UNDRY NOTICES	AND REPORTS ON	WELLS	NY RESERVOIR.		
031					7. Unit Agreement Name	
OIL GAS WELL	X) OTHER				<u> </u>	
					8. Farm or Lease Name	
MESA PETROLEUM CO.					FELL ESTATE	
	TOLLOIT GOT				9. Well No.	
Address of Colerator	CHN RUITI DING/M	IDLAND TX 7970	01		1	
					IC. Field and Pool, or Wildea	t
. Location of Well	1000	HTILOS		1980	WILDCAT ABO	
UNIT LETTER	1900	FROM THE	LINE AND	FEET FROM	THITTING TO	7777
						/////
EAST		TOWNSHIP	RANGE	Z4E NMPN		
*HE					1: County	HH
15. Elevation (Show whether DF, RT, GR, etc.)					CHAVES	
		40	096' GR		WINA 52	77777
	Lask Appendiate	Box To Indicate N	ature of Not	ice, Report or O	ther Data	
			Ţ	SUBSEQUEN	T REPORT OF:	
NOTICE	OF INTENTION T	0.				
		PLUG AND ABANDON	REMEDIAL WORL	. —	ALTERING CASING	
PERFORM REMEDIAL WORK		PLUG AND ABANDON	COMMENCE DRIE	<u></u>	PLUG AND ABANDONI	MENT [
TEMPORARILY ABAHDON		<u></u> -,	l '			
PULL OR ALTER CABING		CHANGE PLANS	CASING "EST AP			
		ا اسم	OTHER	· <u> </u>		
OTHER						
			l and size an	erinent dates includit	ie es imated date of starting any	proposed
17. Describe Froposed or Comp	oleted Operations (Clean	rly state all pertinent dett	aus, and give pe		ig es imated date of starting any	

Spudded well with 17 1/2" hole On 4-7-81. Drilled to 920' and ran 20 jts 13 3/8", 48#, H-40 casing set at 875'. Cemented with 250 sx HLW + 4% CaCl, 100 sx Thixset + 4% CaCl, 250 sx HLW + 4% CaCl, 100 sx Thixset + 4% CaCl, and tailed in with 500 sx "C" + 2% CaCl. Bumped plug with 725 psi. Cement did not circulate. Set one plug with 100 sx Thixset + 4% CaCl, circulated 25 sx to surface. WOC total of 10 hrs, reduced hole to 11" and began drilling ahead dusting on 4-10-81. Drilled to 1705' on 4-11-81, ran 43 jts 8 5/8", 24#, J-55 casing set at 1704'. Cemented with 350 sx HLW + 4% CaCl, 100 sx Thixset + 4% CaCl, 350 sx HLW + 4% CaCl, 100 sx Thixset + 4% CaCl, and tailed in with 300 sx "C" + 2% CaCl. Circulated 150 sx to surface. Tested BOP's and casing to 600 psi for 30 min - 0k. WOC total of 17 hours. Drilled ahead on air 4-12-81.

Regord Ontelliam TITLE OIL AND GAS INSPECTOR		APR 2 0 1981
18. I hereby certify that the Information above is true and complete to the beat of my knowledge and belief. REGULATORY COORDINATOR	DATE	APRIL 13, 1981
USGS (3), TLS, CEN RCDS, ACCTG, ROSWELL, MEC, MAH, PARTNERS, Fil	.E	