

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐ **RECEIVED JUN 01 1981**
2. NAME OF OPERATOR ☒ Yates Petroleum Corporation **O. C. D.**
3. ADDRESS OF OPERATOR **ARTESIA OFFICE**  
207 South 4th St., Artesia, NM 88210
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 330' FNL & 1650' FWL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other) Prod. Casing, Perforate & Treat	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

5. LEASE NM-277916
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME  
North Sturgeon "PR" Federal
9. WELL NO. 1
10. FIELD OR WILDCAT NAME  
Und. San Andres
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Unit C, Sec. 4-T7S-R26E
12. COUNTY OR PARISH Chaves 13. STATE NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3657.2' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

TD 1150'- Ran 28 jts of 4½" 9.5# J-55 casing set at 1150'. Flapper float shoe at 1150'. Cemented w/25 sx 75-25 Poz, .6% D-112, .3% D-65 Tic & 3# KCL. Tailed in w/200 sx 50-50 Poz, .6% D-112, .3% D-65 Tic & 3# KCL. PD 6:00 PM 4-16-81. Bumped plug to 500 psi, released pressure & float held okay. Cement circulated 20 sxs to pit. WOC. WIH w/Steel Strip gun & perforated 1098-1128' w/15 .50" holes. Spotted acid. Set Uni VI 4-1/2" packer at 1042'. Acidized perforations w/2500 gals 15% DS-30 acid & 20 ball sealers. TOOH w/packer. Set pumping equipment. Pumping back load.

**RECEIVED**  
MAY 26 1981  
U. S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct Engineering

SIGNED \_\_\_\_\_ TITLE Secretary DATE 5-20-81

ACCEPTED FOR RECORD (This space for Federal or State office use)  
ROGER A. CHAPMAN  
APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

MAY 26 1981

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

\*See Instructions on Reverse Side