

UNITED STATES. COPY SUBMIT IN TRIPLICATE\*  
DEPARTMENT OF THE INTERIOR (Other instructions on reverse side)  
GEOLOGICAL SURVEY

Form approved.  
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different depth. Use "APPLICATION FOR PERMIT—" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

NM 22615

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

CAMACK FEDERAL

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

UNDESIGNATED ABO

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

SEC 8, T5S, R24E

12. COUNTY OR PARISH 13. STATE

CHAVES

NEW MEXICO

OIL ☐ GAS ☒ OTHER

APR 15 1981

2. NAME OF OPERATOR

Mesa Petroleum Co.

O. C. D.

3. ADDRESS OF OPERATOR

ARTESIA, OFFICE

1000 Vaughn Building / Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)

At surface 1980' FSL & 660' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4067.7' GR

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) 4 1/2" CSG & CEMENT

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

X

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*

Drilled 7 7/8" hole to TD of 4216' on 4-5-81. Ran 102 jts 4 1/2", 10.5#, J-55 casing set at 4163'. Cemented with 700 sx HLW + 10# salt + 1# flocele and tailed in with 300 sx 50-50 Pozmix + 8# salt + 2% gel + 3/10% CFR-2. PD at 4:45 PM 4-5-81. Cement did not circulate. BP at 2700 psi. TOC @ 50'. Released rig @ 6:00 AM 4-6-81. WOCU estimated to arrive 4-20-81.

RECEIVED  
APR 13 1981

18. I hereby certify that the foregoing is true and correct

SIGNED *R. P. Taylor*

TITLE REGULATORY COORDINATOR DATE APRIL 9, 1981

(This space for Federal or State office use)

ACCEPTED FOR RECORD

APPROVED BY PETER W. CHESTER

TITLE DATE

CONDITIONS OF APPROVAL, IF ANY:

XC: USGS (3), MPR 141081, PARTNERS, FILE, ROSWELL

U.S. GEOLOGICAL SURVEY See Instructions on Reverse Side  
ROSWELL, NEW MEXICO