

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

C/SF

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		5. LEASE DESIGNATION AND SERIAL NO. NM 33266	
2. NAME OF OPERATOR MESA PETROLEUM CO. ✓		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR 1000 VAUGHN BUILDING/ MIDLAND TX 79701		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' FNL & 1980' FEL		8. FARM OR LEASE NAME HUGGINS FEDERAL	
14. PERMIT NO.		9. WELL NO. 2	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4127.5' GR		10. FIELD AND POOL, OR WILDCAT UNDESIGNATED ABO	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA SEC. 17, T5S, R24E	
		12. COUNTY OR PARISH CHAVES	
		13. STATE NEW MEXICO	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐PULL OR ALTER CASING ☐FRACTURE TREAT ☐MULTIPLE COMPLETE ☐SHOOT OR ACIDIZE ☐ABANDON* ☐REPAIR WELL ☐CHANGE PLANS ☐(Other) ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐REPAIRING WELL ☐FRACTURE TREATMENT ☐ALTERING CASING ☐SHOOTING OR ACIDIZING ☐ABANDONMENT* ☐(Other) SPUD & 13 3/8" CSG ☒(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded well with 17 1/2" hole on 4-10-81. Drilled to 920' and ran 23 jts 13 3/8", 48#, H-40 casing set at 919'. Cemented with 250 sx LW + 4% CaCl, 100 sx Thixset + 4% CaCl, 200 sx LW + 4% CaCl, 100 sx Thixset + 4% CaCl, and tailed in with 500 sx "C" + 3% CaCl. Circulated 5 sx to surface. WOC total of 9 1/2 hours. Reduced hole to 11" and drilled ahead on 4-12-81.

XC: USGS (3), TLS, CEN RCDS, ACCTG, MEC, MAH, PARTNERS, FILE, ROSWELL

18. I hereby certify that the foregoing is true and correct

SIGNED

R. F. Martin

TITLE

REGULATORY COORDINATOR

DATE

APRIL 13, 1981

(This space for Federal or State Office Use)

APPROVED BY

PETER W. CHESTER

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

APR 14 1981

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

See Instructions on Reverse Side