

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIP. DATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 33266

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

HUGGINS FEDERAL

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

UNDESIGNATED ABO

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

SEC 17, T5S, R24E

12. COUNTY OR PARISH

CHAVES

13. STATE

NEW MEXICO

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

MESA PETROLEUM CO.

3. ADDRESS OF OPERATOR

1000 VAUGHN BUILDING/MIDLAND TX 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface

660' FNL & 1980' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4127.5' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) 8 5/8" CSG & CEMENT

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 11" hole to 1720' and ran 53 jts 8 5/8", 24#, K-55 casing set at 1711'. Cemented with 250 sx LT + 1# Flocele + 4% CaCl, 100 sx Thixset + 4% CaCl, 250 sx LT + 1# Flocele + 4% CaCl, 100 sx Thixset + 4% CaCl, and tailed in with 500 sx "C" + 3% CaCl. Circulated 150 sx to surface. WOC 10 hours, then tested BOP's and casing to 600 psi for 30 min - OK. Reduced hole to 7 7/8" and drilled ahead on 4-14-81.

XC: USGS (3), TLS, ROSWELL, MEC, PARTNERS, FILE

18. I hereby certify that the foregoing is true and correct

SIGNED R. E. NathanTITLE REGULATORY COORDINATORDATE APRIL 16, 1981

(This space for Federal or State office use)

APPROVED BY

PETER W. CHESTER

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

APR 21 1981

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

See Instructions on Reverse Side

APR 20 1981
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO