

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	

RECEIVED

JUN 4 1981

5a. Indicate Type of Lease	
State ☒	Fee ☐
5. State Oil & Gas Lease No.	
LG 3591	

SUNDARY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT DEPTH OR TO ABANDON A WELL. USE APPLICATION FOR PERMIT, FORM C-101 FOR SUCH PROPOSALS.)

ARTESIA, OFFICE

6. Indicate Type of Well		7. Unit Agreement Name	
OIL WELL ☒	GAS WELL ☐		
8. Name of Operator		8. Farm or Lease Name	
Yates Petroleum Corporation		Tamarack "QF" State	
9. Address of Operator		9. Well No.	
207 South 4th St., Artesia, NM 88210		1	
10. Location of Well		10. Field and Pool, or Wildcat	
UNIT LETTER D 330 FEET FROM THE North LINE AND 990 FEET FROM West		Unders. San Andres	
THE West LINE, SECTION 32 TOWNSHIP 6S RANGE 26E NMPM.			
11. Elevation (Show whether DF, RT, GR, etc.)		12. County	
3658' GR		Chaves	

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REAM WORK ☐

TEMPORARILY ABANDON ☐

PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐

CHANGE PLANS ☐

REMEDIAL WORK ☐

COMMENCE DRILLING OPNS. ☐

CASING TEST AND CEMENT JOB ☒

OTHER ☐

ALTERING CASING ☐

PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 14-3/4" hole at 2:15 AM 5-1-81. Reaming 7-7/8" hole to 9-1/2" hole from 350' to 762'. Lost circulation at 697'. TD 350'- Ran 9 joints of 10-3/4" 32# ST&C J-55 casing set at 350'. 1-regular pattern guide shoe at 350'. Flapper float at 310'. Cemented w/350 sacks Class C 4% CaCl. Compressive strength of cement - 1250 psi in 12 hrs. PD 6:00 AM 5-2-81. Bumped plug to 500 psi, released pressure & float held okay. Cement circulated 25 sacks to pit. WOC 12 hrs. Reduced hole to 7-7/8". TD 798'- Ran 19 joints of 7" 20# J-55 casing set at 798'. 1-regular pattern guide shoe at 798'. Flapper insert float at 764'. Cemented w/100 sacks Class C Neat, 400 sacks 65-35 Poz, 4% D-20 gel, 8# Kolite, 1/4# celloflakes & 3% CaCl. Tailed in w/100 sacks Class C 2% CaCl. PD 4:15 PM 5-5-81. Bumped plug to 700 psi, released pressure & float held okay. Cement did not circulate. WOC 6 hrs. Ran Temperature Survey & found top of cement at 700'. Ran 1". Tagged cement at 700'. Spotted 25 sacks Class C 4% CaCl. PD 2:43 PM 5-5-81. WOC 2 hours. Ran 1". Tagged cement at 697'. Spotted 75 sacks Class C 4% CaCl. PD 9:28 PM 5-5-81. WOC 4 hrs. Ran 1". Tagged cement at 651'. Spotted 25 sacks Class C 4% CaCl. PD 1:47 AM 5-6-81. WOC 3 hrs. Ran 1". Tagged cement at 620'. Spotted 25 sacks Class C 4% CaCl. PD 5:23 AM 5-6-81. WOC 2-1/2 hrs. Ran 1". Tagged cement at 610'. Spotted 25 sacks Class C 4% CaCl. PD 8:16 AM 5-6-81. WOC 4 hrs. Ran 1". Tagged cement at 570'. Spotted 50 sacks Class C 4% CaCl. PD 12:28 PM 5-6-81. WOC 2-1/2 hrs. Ran 1". Tagged cement at 632'. Spotted 25 sacks Class C 4% CaCl. PD 3:04 PM 5-6-81. WOC 3 hrs. Ran 1". Tagged cement at 650'. Spotted 25 sacks Class C 4% CaCl. PD 6:11 PM 5-6-81. WOC 15 hrs. (cont'd)

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED _____ TITLE Engineering Secretary DATE 5-29-81

APPROVED BY Mr. Williams TITLE OIL AND GAS INSPECTOR DATE JUN 10 1981

CONDITIONS OF APPROVAL, IF ANY:

(cont'd)

Tamarack "QF" State #1-LG-3591
Unit D, 330 FNL & 990 FWL,
Sec. 32-6S-26E
Chaves County, NM

Ran 1". Tagged cement at 575'. Spotted 20 sacks Class C 4% CaCl. PD 11:15 AM 5-7-81. WOC 1 hour & 15 minutes. Ran 1". Tagged cement at 575'. Spotted 20 sacks Class C 4% CaCl. PD 12:46 PM 5-7-81. WOC 2 hours. Ran 1". Tagged cement at 570'. Spotted 25 sacks Class C 4% CaCl. PD 1:58 PM 5-7-81. WOC 1 hour. Ran 1". Tagged cement at 610'. Spotted 25 sacks Class C 4% CaCl. PD 3:07 PM 5-7-81. WOC 1 hour. Tagged cement at 610'. Spotted 60 sacks Class C 4% CaCl. PD 4:51 PM 5-7-81. WOC 1 hour. Ran 1". Tagged cement at 610'. Spotted 25 sacks Class C 4% CaCl. PD 6:22 PM 5-7-81. WOC 1 hour & 20 minutes. Ran 1". Tagged cement at 610'. Spotted 25 sacks Class C 4% CaCl. PD 7:45 PM 5-7-81. WOC 1 hour & 35 minutes. Ran 1". Tagged cement at 610'. Spotted 25 sacks Class C 4% CaCl. PD 9:35 PM 5-7-81. WOC 1 hour & 30 minutes. Ran 1". Tagged cement at 610'. Spotted 25 sacks Class C 4% CaCl. PD 11:20 PM 5-7-81. WOC 1 hour & 30 minutes. Ran 1". Tagged cement at 610'. Spotted 25 sacks Class C 4% CaCl. PD 1:20 AM 5-8-81. WOC 1 hour & 20 minutes. Ran 1". Tagged cement at 570'. Spotted 20 sacks Class C 4% CaCl. PD 2:55 AM 5-8-81. WOC 1 hour & 30 minutes. Ran 1". Tagged cement at 440'. Spotted 20 sacks Class C 4% CaCl. PD 4:40 AM 5-8-81. WOC 1 hour & 20 minutes. Ran 1". Tagged cement at 300'. Spotted 30 sacks Class C 4% CaCl. PD 6:10 AM 5-8-81. WOC 5 hours & 10 minutes. Ran 1". Tagged cement at 130'. Spotted 25 sacks Class C 4% CaCl. PD 11:25 AM 5-8-81. WOC 1 hour & 30 minutes. Ran 1". Tagged cement at 75'. Spotted 25 sacks Class C 4% CaCl. PD 1:05 PM 5-8-81. Circulated 5 sacks to pit. WOC 53 hours and 45 minutes.