

N.M.O.C.D. COPY

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐  
well well

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 660' FNL & FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) Perforate, Squeeze, Production casing.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

TD 1393'. Ran bond log. Indicated questionable bond. USGS ordered the zone of questionable bond to be squeezed. WIH & perforated w/1 .41" hole at 1250'. Squeezed w/75 sacks Class "C". Waited 5 hrs. WIH & perforated w/1 .41" hole at 900'. Squeezed w/425 sacks Class "C". Waited 12 hrs. Ran bond log & reviewed with USGS in Roswell, NM. Bond was okay. Returned to drilling. TD 4300'. Ran 106 jts of 4-1/2" 9.5# K-55 ST&C casing set at 4297'. 1-fill shoe set at 4297'. Cemented w/25 sacks 75/25 Poz, .6% D-112, .3% D-65, 3# KCL, 325 sacks 50/50 Poz, .6% D-112, .3% D-65, 3# KCL. PD 10:30 AM 6-6-81.

Subsurface Safety Valve: Manu. and Type

Set @ . . . . . Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED                      TITLE Engineering Secty DATE 6/24/81

APPROVED BY                       
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD  
ROGER A. CHAPMAN

JUL 1 1981

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

See Instructions on Reverse Side

5. LEASE

USA NM 11799

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

RECEIVED

8. FARM OR LEASE NAME

Hahn "NH" Federal

JUL 7 1981

9. WELL NO.

2

O. C. D.

10. FIELD OR WILDCAT NAME

Und. Abo

ARTESIA OFFICE

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Unit A, Sec. 9-T7S-R25E

12. COUNTY OR PARISH 13. STATE

Chaves

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3834.6' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

RECEIVED  
JUN 25 1981  
OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

UNITED STATES N.M.O.C.D. **COPY**  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐  
well well

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 660' FNL & FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) Perforate, Squeeze, Production casing.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

TD 1393'. Ran bond log. Indicated questionable bond. USGS ordered the zone of questionable bond to be squeezed. WIH & perforated w/1 .41" hole at 1250'. Squeezed w/75 sacks Class "C". Waited 5 hrs. WIH & perforated w/1 .41" hole at 900'. Squeezed w/425 sacks Class "C". Waited 12 hrs. Ran bond log & reviewed with USGS in Roswell, NM. Bond was okay. Returned to drilling. TD 4300'. Ran 106 jts of 4-1/2" 9.5# K-55 ST&C casing set at 4297'. 1-fill shoe set at 4297'. Cemented w/25 sacks 75/25 Poz, .6% D-112, .3% D-65, 3# KCL, 325 sacks 50/50 Poz, .6% D-112, .3% D-65, 3# KCL. PD 10:30 AM 6-6-81.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Engineering Secty DATE 6/24/81

ACCEPTED FOR RECORD (This space for Federal or State office use)  
ROGER A. CHAPMAN

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

JUL 1 1981

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

See Instructions on Reverse Side

5. LEASE

USA NM 11799

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Hahn "NH" Federal

9. WELL NO.

2

10. FIELD OR WILDCAT NAME

Und. Abo

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Unit A, Sec. 9-T7S-R25E

12. COUNTY OR PARISH

Chaves

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3834.6' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

RECEIVED  
JUN 25 1981  
OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO