

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

NOV 3 1982

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☐ other ☒ DRY

2. NAME OF OPERATOR

MESA PETROLEUM CO. ✓

3. ADDRESS OF OPERATOR

1000 VAUGHN BLDG.

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 1980' FSL & 660' FEL

AT SURFACE:

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH: SAME

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>
(other)	<input type="checkbox"/>

SUBSEQUENT REPORT OF:

<input type="checkbox"/>
<input type="checkbox"/>
<input type="checkbox"/>
<input type="checkbox"/>
<input type="checkbox"/>
<input type="checkbox"/>
<input type="checkbox"/>
<input type="checkbox"/>
<input checked="" type="checkbox"/>

RECEIVED
JUL 15 1981OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

LEASE

NM 36645

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

HUB FEDERAL

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

UNDESIGNATED ABO

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 6, T9S, R23E

12. COUNTY OR PARISH

CHAVES

13. STATE

NEW MEXICO

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3956.6' GR

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

P & A'd well 7-8-81 as follows:

Set 175 sx HLW + 2% CaCl from 3700'-2650' from TD to top of ABO

Set 25 sx "C" + 2% CaCl from 1810'-1710' across 8 5/8" csg shoe.

Set 30 sx "C" + 2% CaCl from 97' to surface.

Rig released 6:00 a.m. 7-9-81

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED R. P. Mook TITLE Regulatory Coord. DATE 7-10-81

APPROVED (This space for Federal or State office use)

APPROVED BY (Orig. Sgd.) PETER W. CHESPEAK TITLE _____ DATE _____CONDITIONS OF APPROVAL, IF ANY: W. CHESPEAK

NOV 2 1982

xc: USGS (3), TLS, GEN RECORDS, ACCTG, ROSWELL, MEC, LAND, PARTNERS, FILE

JAMES A. GILLHAM

DISTRICT SUPERVISOR *See Instructions on Reverse Side