

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Yates Petro Corp.</u>		Lease <u>Conejo RH State</u>		Well # <u>3</u>	
Location of Well	H Unit <u>1950 FNL</u> <u>640 FEL</u>	Section <u>2</u>	Township <u>7</u>	Range <u>25</u>	County <u>Chaves</u>
Drilling Contractor	<u>name #1</u>		Type of Equipment <u>Rotary</u>		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
* <u>15"</u>	<u>10 3/4"</u>	<u>48# J-55</u>		<u>920'</u>	<u>900sx circ.</u>
<u>6 3/4"</u>	<u>5 1/2" or 4 1/2"</u>	<u>15.5# or 10.5#</u>		<u>TD</u>	<u>350sx</u>

Casing Data:

Surface _____ joints of _____ inch _____ # Grade _____
(Approved) (Rejected) _____

Inspected by _____ date _____

Cementing Program

Size of hole 14 3/4" Size of Casing 10 3/4" Sacks cement required _____

Type of Shoe used guide Float collar used insert Btm 3 jts welded yes

TD of hole 926' Set 926' Feet of 10 3/4" Inch 40.5# Grade J-55

New used csg. @ 926' with 300 2% sacks neat cement around shoe
+ 400 sax Western Oil additives 3% cc

Plug down @ 2840 (AM) (PM) Date 12/10/81

Cement circulated yes No. of Sacks 50 sx

Cemented by Western Co. Witnessed by Mike Stubbfield

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: _____

No centralizers

Full returns to TD.