

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

OIL CONSERVATION DIVISION

P. O. BOX 7088

SANTA FE, NEW MEXICO

RECEIVED

Form C-103
Revised 10-1-78

JAN 22 1982

O. C. D.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO ENTER OR TO DEEPEN OR DRILL BACK INTO A VIOLATED RESERVOIR. USE APPLICATION FOR PERMIT TO DRILL FROM C-101 FOR SUCH PROPOSALS.)

OIL WELL ☐	GAS WELL ☒	OTHER ☐	7. Unit Agreement Name
Name of Operator Yates Petroleum Corporation /			8. Form or Lease Name Finley RV Com
Address of Operator 207 South 4th St., Artesia, NM 88210			9. Well No. 1-y
Location of Well UNIT LETTER <u>K</u> <u>1740</u> FEET FROM THE <u>South</u> LINE AND <u>1980</u> FEET FROM THE <u>West</u> LINE, SECTION <u>34</u> TOWNSHIP <u>6S</u> RANGE <u>25E</u> NMPM.			10. Field and Pool, or Wildcat Und. Abo
11. Elevation (Show whether DF, RT, GR, etc.) 3721' GR			12. County Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☒	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☒	

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Set 40' of 14" conductor pipe. Spudded a 12-1/4" hole at 4:00 PM 1-5-82.
Ran 22 joints of 8-5/8" 24# K-55 casing set at 885'. 1-notched guide shoe at 885'.
Float collar (auto-fill) at 845'. Cemented w/200 sacks Thixolite, 2# Permacheck and 1/4# celloseal, 300 sacks Pacesetter Lite, 1/4# celloseal and 1/2# Permacheck.
Tailed in w/200 sacks Class "C" Neat. PD 11:05 PM 1-15-82. Bumped plug to 700 psi, released pressure and float held okay. Cement did not circulate. WOC 6 hours. Ran Temperature Survey and found top of cement at 800'. Ran 1". Tagged cement at 240'.
Spotted 50 sacks Class "C" 3% CaCl₂. PD 2:10 PM 1-16-82. WOC 2 hours. Ran 1". Tagged cement at 240'.
Spotted 50 sacks Class "C" 3% CaCl₂. PD 2:10 PM 1-16-82. WOC 2 hours. Ran 1". Tagged cement at 240'.
Spotted 50 sacks Class "C" 3% CaCl₂. PD 4:30 PM 1-16-82. WOC 5 hours. Filled hole with 8 yards of Ready-Mix. Circulated 1 yard to surface. WOC.
Drilled out 7:00 AM 1-18-82. WOC 55 hours and 55 minutes. Nippled up and tested to 1000 psi, OK. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

14. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Mike Williams</u>	TITLE <u>Engineering Secretary</u>	DATE <u>1-22-82</u>
APPROVED BY <u>Mike Williams</u>	TITLE <u>OIL AND GAS INSPECTOR</u>	DATE <u>JAN 25 1982</u>
CONDITIONS OF APPROVAL, IF ANY:		