

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

RECEIVED

MAR 24 1982

O. C. D.
ARTESIA, OFFICE

Form C-103
Revised 10-1-78

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT - FORM C-101 FOR SUCH PROPOSALS.)

OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		1. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation /		3. State Oil & Gas Lease No. LG-0336
4. Address of Operator 207 South 4th St., Artesia, NM 88210		5. Well No. 3
6. Location of Well UNIT LETTER 0 660 FEET FROM THE South LINE AND 1980 FEET FROM THE East LINE, SECTION 26 TOWNSHIP 4S RANGE 24E HMPM.		7. Field and Pool, or Wildcat Und. Abo
8. Elevation (Show whether DF, RT, GR, etc.) 4000' GR		9. County Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/> OTHER <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/> CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/> PLUG AND ABANDONMENT <input type="checkbox"/> OTHER <input type="checkbox"/>
---	--	--	---

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 12-1/4" hole at 11:15 AM 3-14-82. Set 40' of 20" conductor pipe. Ran 23 joints 8-5/8" 24# J-55 casing set at 925'. 1-Texas Pattern notched guide shoe at 925'. Insert float set at 882'. Cemented w/400 sacks Pacesetter "C" with 3% CaCl. Tailed in w/300 sacks Class "C" with 2% CaCl. Cement circulated 25 sacks. PD 2:45 PM 3-15-82. Bumped plug to 750 psi, released pressure and float held okay. WOC. Drilled out 8:45 AM 3-16-82. WOC 18 hours. Nipped up and tested to 1000 psi, released pressure and float held okay. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Engineering Secretary DATE 3-23-82

APPROVED BY M. H. Walker TITLE OIL AND GAS INSPECTOR DATE MAR 25 1982

CONDITIONS OF APPROVAL, IF ANY: