

EXHIBIT H
AUXILIARY EQUIPMENT
Sancors Oil & Gas Company
Mesa Diablo Federal Well No. 1
660' FSL and 660' FEL
Section 35 T.9S R.25E
Chaves County, New Mexico

DRAWWORKS: RATED DEPTH - 7000'

Oilwell 500 (500 HP) 22" Parmac hydromatic brake, 1-1/8" wire line

ENGINES AND DRIVE GROUP:

2 - Cummins NTA - 855P360 (360 HP) with 2 engine compound and twin disc torque converters

PUMPS AND MUD SYSTEM:

- 1 - Cont. Emsco F-1000 (1000 HP) Triplex Pump driven by a D 379 Caterpillar engine.
- 1 - Wilson 600 (600 HP) Duplex Pump driven by a D 379 Caterpillar engine
- 2 - 185 Bbl. mud pits
- 2 - Rumba shale shaker
- 2 - Electric mud agitators

MAST:

Dreco 100' X 15' cantilever mast, 300,000# static hook load capacity w/8 lines, vapor proof lighting

SUBSTRUCTURE:

Box type, 9', 300,000# casing capacity, 250,000# set back, 7.5' clearance below rotary beams, equipped with bogie wheels and 5th wheel to move drawworks, substructure & rotary table intact where locations permit

ROTARY TABLE:

Oilwell 20 1/2"

BLOCK:

Crown - Dreco, 300 ton, 5 sheave, grooved for 1-1/8" wire line

TRAVELING HOOK-BLOCK:

Cont. Emsco Hook-Block 250 Ton Rating - 4 sheave

SWIVEL:

Emsco LA 200, 200 ton

LIGHT PLANT:

- 2 - 135 KW generators, each driven by a Cat 3306 engine, 250 HP each
- 1 - Ingersoll Rand air compressor

BLOWOUT PREVENTERS:

- Sgl QRC - 10" 3000 psi WP
- Sgl QRC - 10" 3000 psi WP
- Choke Manifold - 3000 psi WP

BOP ACCUMULATOR:

Koomey, 80 gal., 3000 psi WP

OTHER EQUIPMENT:

- 4 1/2" Drill Pipe
- Upper Kelly Cock valve
- Kelly, 40 X 4 1/4" square
- Rig floor house
- Change house

- 1 - Toolpushers' bunk house
- Lube oil tank
- Water tank
- 1 - Wireline unit
- 4 Pen recorder

JVL/2/12/81