

UNITED STATES
DEPARTMENT OF THE INTERIOR, NM 88210
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

RECEIVED

1. oil well ☐ gas well ☒ other ☐

2. NAME OF OPERATOR
MESA PETROLEUM CO.

3. ADDRESS OF OPERATOR
O. C. D.
1000 VAUGHN BUILDING/MIDLAND TX 79701-4493

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
660' FNL & 990' FWL
AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: SAME

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

(other) Spud, 8 5/8" CSC / cement

RECEIVED
JUN 21 1982
OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3557' GR

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded well with 14 3/4" hole on 6-9-82. Drilling with mud, lost circulation at 553' and again at 691'. Drilled to 955' and attempted to run casing but hole caved in. Set 400 sxs Thixalite + 1/2#/sx flocele + 4% CaCl to condition hole on 6-10-82. Set additional plugs on 6-11-82 to 6-13-82 to control hole conditions. Tried to run 10 3/4" csg without success on 6-15-82. Washed hole & failed to run 10 3/4" casing - wouldn't go. Washed to 950' and ran 23 jts 8 5/8" casing set at 948'. Cemented with 700 sxs Thixalite + 1/2#/sx flocele + 4% CaCl and filled in with 200 sxs Class "C" + 2% CaCl. PD at 1:30 PM, 6-16-82. Cement did not circulate. Ran temperature survey --- TOC at 100'. Set two plugs with a total of 600 sxs Class "C" + 4% CaCl to circulate cement. Tested BOP's and casing at 600 psi for 30 mins -- OK. Reduced hole to 7 7/8" and drilled ahead on 6-17-82. 700 total 18 hours.

XC: MMS (7), TLS, CEN RCDS, ACCTG, MEC, ROSWELL, REM, FILE, (PARTNERS)
Subsurface Safety Valve: Manu. and Type _____

18. I hereby certify that the foregoing is true and correct

SIGNED R.P. [Signature] TITLE REGULATORY COORDINATOR

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

SEP 29 1982

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side