Form 3160-5 (June 1990)

UNITED STATES Artesia, NM 892 CEIVE

DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

1111 28 1997

FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993

5. Lease Designation and Serial No.

	_	_	_	_	_
NM-	1	a	1	Q	7
TAT.T.	ı	J	1	u	1

SUNDRY NOTICES AND REPORTS ON WELLS

6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT-" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well Oil X Gas 8. Well Name and No. Other 2. Name of Operator Long Arroyo MQ Fed. #2 (505) 748-1471)9. API Well No. YATES PETROLEUM CORPORATION : 3. Address and Telephone No. 30-005-61701 10. Field and Pool, or Exploratory Area 105 South 4th St., Artesia, NM 88210 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Springer Basin Atoka-Morrow 11. County or Parish, State 660' FNL & 990' FEL of Section 26-T14S-R27E Chaves Co., NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Change of Plans New Construction Recompletion Subsequent Report Non-Routine Fracturing Plugging Back Casing Repair Water Shut-Off Final Abandonment Notice Altering Casing Conversion to Injection Other Add pay in Morrow & Dispose Water (Note: Report results of multiple completion on Well Atoka Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Propose to add pay in Morrow and Atoka Sands as follows: Install standing valve in Guiberson 1.875" on/off tool at 8018'. Load tubing with KCL water and test to 2500#. Load annulus and test to 500#. Install BOP and get off on/off tool. TOOH w/tubing. Perforate 7992-7995' w/8 holes (2 SPF) (Morrow). Straddle perfs. 7992-7995' and acidize with 1000 gallons 7-1/2% Morflow (Morrow) acid containing 1000 scf/bbl N2 and ball sealers. Swab back. Frac if necessary with binary or 30% CO2 gel & 10000-15000# 20-40 resin coated sand. Perforated 7903-7918' w/24 holes (2 SPF) (Atoka). Straddle 7903-7918' and acidize with 2000 gallons 7-1/2% Morflow (Morrow) acid containing 1000 scf/bbl ni ball sealers. Swab back. Frac if necessary with binary or 30% CO2 gel & 25000-3000 coated sand. TOOH w/RBP and packer. TIH w/packer with on/off tool and swab well IUIProduction Clerk Approved by _______ Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. *See Instruction on Reverse Side