

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☐ Gas Well ☒ Other P&A

2. Name of Operator

YATES PETROLEUM CORPORATION (505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit B, 660' FNL & 1980' FEL, Sec. 3-T5S-R24E

5. Lease Designation and Serial No.

NM 22614

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Mike Harvey TR Fed. #2

9. API Well No.

30-005-61776

10. Field and Pool, or Exploratory Area

Pecos Slope Abo

11. County or Parish, State

Chaves, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

2-7-92. Notified Stan Mayo, BLM, Roswell, NM of plans to P&A well on Monday, 2-10-92.
2-10-92. Load well, release tension packer. POH with 110 jts 2-3/8" tubing. RIH with 4 1/2" CIBP and set at 3500'. RIH w/110 jts tubing and tagged bridge plug.
2-12-92. Pumped 56 BMLF to load hole. Mixed and pumped 5 sx Class "C" cement and displace w/13 BMLF. Plug from 3428-3500'. Laid down 61 jts tubing. Pumped 25 sx cement and displace w/4.5 BMLF. Stand back tubing. WOC. NOTE: Vic Coates, BLM, Roswell, NM, witnessed. RIH w/tubing and did not tag plug. Vic Coates advised to spot another plug. Mixed another 25 sx cement and spot from 1570-1210' and displace w/4.5 BMLF. Stand back tubing. SI. WOC. RIH with 34 jts tubing and tagged top of cement at 1086'. NOTE: Vic Coates, BLM, Roswell, NM, witnessed tagging of plug at 1086'. Plug from 1570-1086'. POH and laid down 26 jts tubing to 150'. Pumped 10 sx Class "C" cement and set surface plug. Cleaned out lines and BOP. RD and moved out. Installed dry hole marker.

WELL PLUGGED & ABANDONED 2-13-92.

Approved as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct

Signature *[Signature]*

Title Production Supervisor

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title _____

Date _____

MAR 27 1992

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side