

c/sf

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Drawer DD

Artesia, NM 884105. LEASE

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen a well back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐ OCT 18 1982

2. NAME OF OPERATOR

MESA PETROLEUM CO. ✓ O. C. D.

3. ADDRESS OF OPERATOR

ARTESIA OFFICE

P O BOX 2009/AMARILLO, Texas 79189

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1880' FNL; 1980' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON* ☐

(other) Spud, 8 5/8" Csg & Cement

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

MAXINE FEDERAL

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Wildcat ABO

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 20, T7S, R22E

12. COUNTY OR PARISH

Chaves

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

4404' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded well with 12 1/4" hole on 10-3-82, lost returns on FW at 92'. Drilled to 1308' and ran 30 jts, 8 5/8", 24#, K55 casing set at 1308'. Cemented with 700 sx HLW + 1/4# flocele + 4% CaCl and tailed in with 200 sx "C" + 2% CaCl. PD at 5:30 P.M. 10-4-82. Cement did not circulate. Ran temp survey--TOC at 630', set sixteen plugs with a total of 2825 sx "C" + 4% CaCl and 15 yards of redi-mix to circulate cement. Tested BOP's and casing to 600 psi for 30 min--OK. Reduced hole to 7 7/8" and drilled ahead with FW on 10-7-82. WOC total of 55 hours

RECEIVED

OCT 12 1982

Subsurface Safety Valve: Manu. and Type

OIL & GAS
Set @
MINERAL INT. SERVICE
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

R.E. [Signature]

TITLE Regulatory Coord.

DATE 10-8-82

ACCEPTED FOR RECORD

(This space for Federal or State office use)

(ORIG. SGD.) DAVID R. GLASS

APPROVED BY

CONDITIONS OF APPROVAL IF ANY

OCT 14 1982

TITLE

DATE

XC: MMS-R(0+2), Cen Reds, Acctg, REM(File), Midland, Roswell, Partners ()

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

See Instructions on Reverse Side