NM OIL CONS. COMMI LOND

Drawer DD 5. LEASE

| Form A | pproved | ١.  |         |   |
|--------|---------|-----|---------|---|
| Budget | Bureau  | No. | 42-R142 | 4 |

| DEPARTMENT OF THE INTERIORSIA, NM 88  | 2000-16803-A   |
|---|--|
| GEOLOGICAL SURVEY   | 6. IF INDIAN, ALLOTTEE OR TRIBE NAME   |
| SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)                         | 7. UNIT AGREEMENT NAME RECEIVED  |
|   | -Ir 1 10 10 10 10 10 10 10 10 10 10 10 10 1  |
| 1. oil gas □ other  | 9. WELL NO. APR 1 5 1983   |
| 2. NAME OF OPERATOR   | O.C.D.   |
| Robert N. Enfield   | 10. FIELD OR WILDCAT NAMERIESIA, OFFICE  |
| 3. ADDRESS OF OPERATOR<br>P.O. Box 2431, Santa Fe, NM 87501   | 11. SEC., T., R., M., OR BLK. AND SURVEY OF  |
| 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17  | AREA   |
| below.) 2307  | Sec. 35, T9S, R29E   |
| AT SURFA <u>CTO7</u> ' FNL & 1651' FEL of Sec. 35<br>AT TOP PROD. INTERVAL:   | 12. COUNTY OR PARISH 13. STATE A TECHNOLOGY  |
| AT TOTAL DEPTH:   | 14. API NO.  |
| 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA   |  |
| REFORT, OR OTHER DATA   | 15. ELEVATIONS (SHOW DF, KDB, AND WD)   3961 GR  |
| REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:  |  |
| TEST WATER SHUT-OFF L   |  |
| SHOOT OR ACIDIZE  | <b>心尼亞斯斯斯</b>  |
| REPAIR WELL   | (NOTE: Report results of multiple completion or zon<br>change of Form 9–330.)  |
| MULTIPLE COMPLETE   |  |
| CHANGE ZONES  | OCT 15 1982  |
| (other)   | r" & 6.53  |
| 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly starincluding estimated date of starting any proposed work. If well is a measured and true vertical depths for all markers and zones pertine | directionally drilled, give subsurface locations and   |
| Plugging Operations: TD 2050', pumped a total of Halliburton Class "C" cement.  | f 130 sacks of the same of the |
| Plug #1: 100 feet cement at 1930'<br>Plug #2: 100 feet cement at 1308'<br>Plug #3: 100 feet cement at 440'<br>10 sx cement at top of 8-50   | S" casing.   |
| Released rig at 13:30 AM October 4, 1<br>Pits have been fenced. Waiting on lo   | 982. Cation to dry out.  |
| Subsurface Safety Valve: Manu. and Type   | Set @F1  |
| . 18. I herehy certify that the foregoing is true and correct   |  |
|   | DATE 10/13/82  |
| APPROVED (This space for Federal or State of  | ffice use)   |
| APPROVIDER S.A.) PETER W. CHISTER TITLE CONDITIONS OF APPROVAL, IF ANY:   | DATE   |
| APR 1 4 1983  |  |
| *** ** "  | $\mathcal{F}_{\mathcal{F}}}}}}}}}}$   |