

OCT 27 1982

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Drawer DD
Roswell, NM 88210

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐

2. NAME OF OPERATOR

DEPCO, Inc.

3. ADDRESS OF OPERATOR

870 Centmal, Odessa, Texas 79761

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

C-660' FNL & 1980' FWL, Sec. 18,
AT SURFACE: T-5S, R-25E

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) Spud & S. C.

5. LEASE

NM 15289

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Benedict Federal Com.

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Pecos Slopes ABO

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 18, 5, 25

12. COUNTY OR PARISH

Chaves

New Mex.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3914 ft

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

RECEIVED

OCT 25 1982

OIL & GAS
MINERALS MGMT. SERVICE
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10-13-82 Drld. 14 3/4" hole to 978'. Ran 25 jts. 10 3/4" 40.50# J-55 csg. set @ 975'. Cmtd. w/565 sx. BJ Lite w/1/4# Celoflake, 2% CaCl. Followed w/200 sx. Class "C" w/2% Ca Cl. Plug down @ 8:30 pm. Circ. 75 sx.

10-14-82 Tested pipe & BOP @ 1000# for 30 min. Tested OK.

10-21-82 Drld. 7 7/8" hole to 4250' TD. Ran 107 jts. 4 1/2" 10.50# J-55 csg. set @ 4249'. Cmtd. w/450 sx. 50-50 pozmix w/2% gel, 5# salt, .3 of 1% D-19, .3 of 1% D-31, .10 of 1% D-6. Opened DV tool @ 2188' & Circ. 4 hrs. Cmtd. 2nd stage w/525 sx. BJ Lite w/2% Ca Cl. Followed w/450 sx. 50-50 Pozmix w/2% gel & 2% CaCl. Plug down. @ 5:50 am 10-22-82. Circ. 55 sx.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED David R. Glass Chief Prod. Clerk DATE 10-22-82

ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL

(ORIG. SGD.) DAVID R. GLASS

OCT 26 1982

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

ACCEPTED FOR RECORD

201 10 100

100 10 100