

UNITED STATES <sup>Artesia, NM 88210</sup>  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other

2. NAME OF OPERATOR  
Mesa Petroleum Co.

3. ADDRESS OF OPERATOR  
P.O. Box 2009 /Amarillo, Texas 79189

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 1980' FNL & 660' FWL  
AT SURFACE:  
AT TOP PROD. INTERVAL: same  
AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) TD, 4 1/2" CSG & Cement

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE  
NM-15289

6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
RECEIVED

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Crowley Federal

9. WELL NO.  
1 ARTESIA, OFFICE

10. FIELD OR WILDCAT NAME  
Pecos Slope ABO

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec 8, T5S, R25E

12. COUNTY OR PARISH  
Chaves

13. STATE  
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3882' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled 9 7/8" hole to 1749' and then reduced hole to 7 7/8". Drilled with mud to TD of 4000' on 11-1-82. Ran 99 jts of 4 1/2", 10.5#, K55, ST&C Casing set at 4000'. Cemented with 1100sx HLW + 5# Salt + 1/4# Flocele and tailed in with 400 sx "C" + 5# KCL + 3/10% Halad + 2/10% CFR-2. PD at 1100 hours 10-2-82. Ran temp survey - - TOC at 1700'. Rig released at 2000 hours 11-2-82. WOCU

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED R. P. Mathis TITLE Regulatory Coordinator DATE 11-5-82

ACCEPTED FOR RECORD

(ORIG. SGD.) DAVID R. CLASS

APPROVED BY  
CONDITIONS OF APPROVAL

XC: MMS-R (046), CEN RCDS, ACCTG, BRR, REM (FILE)

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

See Instructions on Reverse Side

RECEIVED

NOV 9 1982  
OIL & GAS  
MINERALS MGMT. SERVICE  
ROSWELL, NEW MEXICO