

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Drawer DD
Artesia, NM 88210

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR
Yates Petroleum Corporation

3. ADDRESS OF OPERATOR
207 S. 4th, Artesia, New Mexico 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 990' FSL and 990' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other)

☒
☐
☐
☐
☐
☐
☐
☐

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 14-3/4" hole 10:00 AM 11-20-82. Set 80' of 20" conductor pipe. Ran 15 joints of 10-3/4" 40.5# J-55 casing set 607'. 1-Texas Pattern notched guide shoe set 607'. Insert float set 563'. Cemented with 400 sacks Pacesetter Lite, 1/4# flocele, 3% CaCl₂. Tailed in with 250 sacks Class "C" with 2% CaCl₂. Compressive strength of cement-1050 psi in 12 hours. PD 4:15 AM 11-22-82. Bumped plug to 1000 psi, released pressure and float held okay. Cement did not circulate. Casing stuck 607'. WOC 6 hours. Ran Temperature Survey and found top of cement 200'. Ran 1". Spotted 175 sacks Class "C" 2% CaCl₂. PD 2:00 PM 11-22-82. Cement circulated 25 sacks to pit. WOC. Drilled out 10:15 PM 11-22-82. WOC 18 hours. Nippled up and tested to 1000#, OK. Reduced hole to 9-7/8". Drilled plug and resumed drilling.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct.

Production
Supervisor

SIGNED

DATE 11-24-82

APPROVED BY
CONDITIONS OF APPROVAL

(ORIG. SGD.) DAVID R. GLASS

DEC 01 1982

MINERALS MANAGEMENT SERVICE
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side

RECEIVED

NOV 30 1982

OIL & GAS
MINERALS MGMT. SERVICE
ROSWELL, NEW MEXICO