YATTS PETROLEUM CORPORATION <u>H</u> ris "VR" Federal #1 660' FSL and 660' FEL Sec. 8-T10S-R25E

In conjunction with Form 9-331C, Application for Persit to Drill subject well, Yates Petroleum Corporation submits the following ten items of pertinent information in accordance with USGS requirements.

- 1. The geologic surface formation is sandy alluvium
- 2. The estimated tops of geologic markers are as follows:

San Andres	605'	
Glorieta	1416'	
Fullerton	2836'	
Abo	3572'	
TD	4350'	
		· · · · · · · · · · · · · · · · · · ·

3. The estimated depths at which anticipated water, oil or gas formations are expected to be encountered:

Water: _250'-300'

Oil or Gas: Abo 3600'

- 4. Proposed Casing Program: See Form 9-331C.
- 5. Pressure Control Equipment: See Form 9-331C and Exhibit B.
- 6. Mud Program: See Form 9-331C.
- 7. Auxiliary Equipment: Kelly Cock; pit level indicators and flow sensor equipment; sub with full-opening valve on floor, drill pipe connection.
- 8. Testing, Logging and Coring Program:

	Surface casing to TD.
DST's:	As warranted.
Coring:	None anticipated.
Logging:	CNL-FDC TD to csg w/GR-CNL to surface, DLL from TD to casing .

- 9. No abnormal pressures or temperatures are anticipated.
- 10. Anticipated starting date: As soon as possible after approval.