

RECEIVED

NOV 3 1982

O. C. D.
ARTESIA, OFFICE

SUPPLEMENTAL DRILLING DATA

ISLER EXPLORATION, INC.
No.1 Wolf Federal
2080'FSL 330'FWL Sec.25-4S-25E
Chaves County, N.M.

NM 17036

The following items supplement Form 9-331C in accordance with instructions contained in NTL-6.

1. SURFACE FORMATION: Seven Rivers

2. ESTIMATED TOPS OF GEOLOGIC MARKER:

San Andres	700'
Glorieta	1500'

3. ESTIMATED DEPTHS TO WATER, OIL OR GAS FORMATION:

Fresh Water	-	Surface to 950'
Oil	-	1100'

4. PROPOSED CASING PROGRAM:

11 3/4" Casing	-	30' Joint, grouted to surface.
8 5/8" Casing	-	950' Cemented to the surface.
4 1/2" Casing	-	Set to total depth and cement- ed back into the surface casing.

5. PRESSURE CONTROL EQUIPMENT: A double-ram 3000#W.P. blow-out preventer will be installed prior to drilling below the surface casing.

6. CIRCULATING MEDIUM: Native mud will be used as the circulating medium. Additives will be used as necessary to maintain proper mud characteristics.

7. AUXILIARY EQUIPMENT: Full-opening kelly cock, to fit the drill string in use, will be kept on the rig floor at all times.

8. TESTING, LOGGING AND CORING PROGRAM:

Samples:	Samples will be obtained from surface to TD
DST:	None anticipated
Logging:	GR-CNL from surface to TD
	FDC log from surface casing to TD
Coring:	None anticipated