

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Artesia, NM 88210

LEASE

NM 28305

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Binnion TT Federal

9. WELL NO.

5

JAN 05 1983

10. FIELD OR WILDCAT NAME
Pecos Slope Abo

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Unit C, Sec. 24-T7S-R25E

12. COUNTY OR PARISH
Chaves

13. STATE
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3679' LGR

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 660 FNL & 1980 FWL, Sec. 24-7S-25E

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

PULL OR ALTER CASING

MULTIPLE COMPLETE

CHANGE ZONES

ABANDON*

(other)

RECEIVED

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

DEC 28 1982

OIL & GAS

MINERALS MGMT. SERVICE

POSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Give pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spudded a 14-3/4" hole at 4:00 AM 12-18-82. Ran 28 jts of 10-3/4" 40.5# J-55 casing set at 850'. 1-Texas Pattern notched guide shoe set at 850'. Insert float set at 826'. Cemented w/400 sacks Pacesetter Lite, 1/4# celloseal, 3% CaCl₂. Tailed in w/300 sacks Class "C" 2% CaCl₂. Compressive strength of cement - 1250 psi in 12 hours. PD 5:30 AM 12-21-82. Bumped plug to 900 psi, released pressure and float held okay. Cement circulated 50 sacks. WOC. Drilled out 11:30 PM 12-21-82. WOC 18 hours. Nipped up and tested to 1000 psi for 30 minutes, okay. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

Production

SIGNED

TITLE Supervisor

DATE 12-27-82

ACCEPTED FOR RECORD

(ORIG. SGD.) DAVID R. GLASS

(For Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL IF ANY

TITLE

DATE

JAN 04 1983

MINERALS MANAGEMENT SERVICE
POSWELL, NEW MEXICO

*See Instructions on Reverse Side

100-100000

