## STATE OF NEW MEXICO

AGT AND WHITE PIACE D	1	
DISTRIBUTION	+	F
BANTA FE		<u> </u>
rice	V	2000
U.1.0.1,		
LAND DEFICE	Ĭ	
		7

	OIL CONSERVATI	ON DIVISION	
DISTRIBUTION	P O. BOX 2	088	Form C-103
BANTA PE	SANTA FE, NEW M	EXICO 87501 RECEIVED	Revised 10-1-73
one be		ter car.	5a. Indicate Type of Lease
U.1.O.1,			State For
LAND OFFICE		MAR 3 0 1983	5. State Oil & Gas Lease No.
OPERATOR	]		5. Sidte (M. & Gos E. Goo No.
		0.0	mmmmm
SUNDR	Y NOTICES AND REPORTS ON WE	LLS O. C. D.	
USE "APPLICAT	POSALS TO DRILL OR TO OLEPEN OR PLUG BACK TON FOR PERMIT -" (FORM C+101) FOR SUCH P	TO A SUSTEMENT ARTESIA, OFFICE	
1.			7. Unit Agreement Name
OIL SAS X	OTHER-		
2. Name of Operator	/		8. Farm or Lease Hame
Mesa Petroleum Co. 🗸			MEC Com
3. Address of Operator			9. Well No.
P.O. Box 2009 / Ama	cillo. Texas 79189		1
4. Location of Well			10. Field and Pool, or Wildcat
	South	660	
UNIT LETTER	560 South	LINE AND FEET FROM	Used abo
West Line, secti	on 6 TOWNSHIP 7S	PANGE 23E	
	15. Elevation (Show whether DF	RT, GR, etc.)	12. County
	///// 4058' GR		Chaves (\\\\\\\
	, , , , , , , , , , , , , , , , , , ,	( ); D ( ).	
	Appropriate Box To Indicate Nat	-	
NOTICE OF I	TENTION TO:	SUBSEQUENT	REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON R	EMEDIAL WORK	ALTERING CASING
TEMPORABILY ABANDON	c	OMMERCE DRILLING OPHS.	PLUG AND ABANDONMENT
PULL DR ALTER CASING	CHANGE PLANS C	ASING TEST AND CEMENT JOB	
_		OTHER TD & 4 1/2" Ca	sing x
OTHER			
17. Describe Proposed or Completed O	perations (Clearly state all pertinent details	, and give pertinent dates, including	estimated date of starting any proposed
work) SEE RULE 1703.			
•		6-83. Ran 78 its 4 17	
Drilled 7 7/8"	hole to TD of 3200' on 3-2		'2", 10.5#, K55,
Drilled 7 7/8" ST&C casing set	hole to TD of 3200' on 3-2 at 3200'. Cemented with	365 sx "C" + 3/10% D-1	'2", 10.5#, K55, .9 + 2/10% D-31 +
Drilled 7 7/8" ST&C casing set 5# KCL. PĎ at	hole to TD of 3200' on 3-2	365 sx "C" + 3/10% D-1	'2", 10.5#, K55, .9 + 2/10% D-31 +
Drilled 7 7/8" ST&C casing set	hole to TD of 3200' on 3-2 at 3200'. Cemented with	365 sx "C" + 3/10% D-1	'2", 10.5#, K55, .9 + 2/10% D-31 +
Drilled 7 7/8" ST&C casing set 5# KCL. PĎ at	hole to TD of 3200' on 3-2 at 3200'. Cemented with	365 sx "C" + 3/10% D-1	'2", 10.5#, K55, .9 + 2/10% D-31 +
Drilled 7 7/8" ST&C casing set 5# KCL. PĎ at	hole to TD of 3200' on 3-2 at 3200'. Cemented with	365 sx "C" + 3/10% D-1	'2", 10.5#, K55, .9 + 2/10% D-31 +
Drilled 7 7/8" ST&C casing set 5# KCL. PĎ at	hole to TD of 3200' on 3-2 at 3200'. Cemented with	365 sx "C" + 3/10% D-1	'2", 10.5#, K55, .9 + 2/10% D-31 +
Drilled 7 7/8" ST&C casing set 5# KCL. PĎ at	hole to TD of 3200' on 3-2 at 3200'. Cemented with	365 sx "C" + 3/10% D-1	'2", 10.5#, K55, .9 + 2/10% D-31 +
Drilled 7 7/8" ST&C casing set 5# KCL. PĎ at	hole to TD of 3200' on 3-2 at 3200'. Cemented with	365 sx "C" + 3/10% D-1	'2", 10.5#, K55, .9 + 2/10% D-31 +
Drilled 7 7/8" ST&C casing set 5# KCL. PĎ at	hole to TD of 3200' on 3-2 at 3200'. Cemented with	365 sx "C" + 3/10% D-1	'2", 10.5#, K55, .9 + 2/10% D-31 +
Drilled 7 7/8" ST&C casing set 5# KCL. PĎ at	hole to TD of 3200' on 3-2 at 3200'. Cemented with	365 sx "C" + 3/10% D-1	'2", 10.5#, K55, .9 + 2/10% D-31 +
Drilled 7 7/8" ST&C casing set 5# KCL. PĎ at	hole to TD of 3200' on 3-2 at 3200'. Cemented with	365 sx "C" + 3/10% D-1	'2", 10.5#, K55, .9 + 2/10% D-31 +
Drilled 7 7/8" ST&C casing set 5# KCL. PĎ at	hole to TD of 3200' on 3-2 at 3200'. Cemented with	365 sx "C" + 3/10% D-1	'2", 10.5#, K55, .9 + 2/10% D-31 +
Drilled 7 7/8" ST&C casing set 5# KCL. PD at 3-27-83.	hole to TD of 3200' on 3-2 at 3200'. Cemented with 1900 3-27-83. Cement did	365 sx "C" + 3/10% D-1 not circulate. Releas	22", 10.5#, K55, 9 + 2/10% D-31 + ed rig at 2400
Drilled 7 7/8" ST&C casing set 5# KCL. PD at 3-27-83.	hole to TD of 3200' on 3-2 at 3200'. Cemented with	365 sx "C" + 3/10% D-1 not circulate. Releas	22", 10.5#, K55, 9 + 2/10% D-31 + ed rig at 2400
Drilled 7 7/8" ST&C casing set 5# KCL. PD at 3-27-83.	hole to TD of 3200' on 3-2 at 3200'. Cemented with 1900 3-27-83. Cement did	365 sx "C" + 3/10% D-1 not circulate. Releas	22", 10.5#, K55, 9 + 2/10% D-31 + ed rig at 2400
Drilled 7 7/8" ST&C casing set 5# KCL. PD at 3-27-83.	hole to TD of 3200' on 3-2 at 3200'. Cemented with 1900 3-27-83. Cement did	365 sx "C" + 3/10% D-1 not circulate. Releas	22", 10.5#, K55, 9 + 2/10% D-31 + ed rig at 2400
Drilled 7 7/8" ST&C casing set 5# KCL. PD at 3-27-83.	hole to TD of 3200' on 3-2 at 3200'. Cemented with 1900 3-27-83. Cement did	365 sx "C" + 3/10% D-1 not circulate. Releas	22", 10.5#, K55, 9 + 2/10% D-31 + ed rig at 2400
Drilled 7 7/8" ST&C casing set 5# KCL. PD at 3-27-83.	hole to TD of 3200' on 3-2 at 3200'. Cemented with 1900 3-27-83. Cement did	365 sx "C" + 3/10% D-1 not circulate. Releas	22", 10.5#, K55, 9 + 2/10% D-31 + ed rig at 2400
Drilled 7 7/8" ST&C casing set 5# KCL. PD at 3-27-83.	hole to TD of 3200' on 3-2 at 3200'. Cemented with 1900 3-27-83. Cement did	365 sx "C" + 3/10% D-1 not circulate. Releas	22", 10.5#, K55, 9 + 2/10% D-31 + ed rig at 2400
Drilled 7 7/8" ST&C casing set 5# KCL. PD at 3-27-83.	hole to TD of 3200' on 3-2 at 3200'. Cemented with 1900 3-27-83. Cement did	365 sx "C" + 3/10% D-1 not circulate. Releas	22", 10.5#, K55, 9 + 2/10% D-31 + ed rig at 2400
Drilled 7 7/8" ST&C casing set 5# KCL. PD at 3-27-83.	thole to TD of 3200' on 3-2 at 3200'. Cemented with 1900 3-27-83. Cement did +2), CEN RCDS, ACCTG, MAT	Got circulate. Release CONT, OPS(FILE), PARTN	22", 10.5#, K55, 9 + 2/10% D-31 + ed rig at 2400
Drilled 7 7/8" ST&C casing set 5# KCL. PD at 3-27-83.	thole to TD of 3200' on 3-2 at 3200'. Cemented with 1900 3-27-83. Cement did +2), CEN RCDS, ACCTG, MAT	365 sx "C" + 3/10% D-1 not circulate. Releas	22", 10.5#, K55, 9 + 2/10% D-31 + ed rig at 2400
Drilled 7 7/8" ST&C casing set 5# KCL. PD at 3-27-83.	thole to TD of 3200' on 3-2 at 3200'. Cemented with 1900 3-27-83. Cement did +2), CEN RCDS, ACCTG, MAT	G65 sx "C" + 3/10% D-1 not circulate. Release CONT, OPS(FILE), PARTN CONT, OPS(FILE), PARTN ULATORY COORDINATOR	22", 10.5#, K55, 9 + 2/10% D-31 + ed rig at 2400
Drilled 7 7/8" ST&C casing set 5# KCL. PD at 3-27-83.	thole to TD of 3200' on 3-2 at 3200'. Cemented with 1900 3-27-83. Cement did +2), CEN RCDS, ACCTG, MAT	Got circulate. Release to circulate. PARTN OPS (FILE), PARTN OPS	ERS  MARCH 29, 1983
Drilled 7 7/8" ST&C casing set 5# KCL. PD at 3-27-83.	thole to TD of 3200' on 3-2 at 3200'. Cemented with 1900 3-27-83. Cement did +2), CEN RCDS, ACCTG, MAT  The above is true and complete to the best of recommendation in the second secon	G65 sx "C" + 3/10% D-1 not circulate. Release CONT, OPS(FILE), PARTN CONT, OPS(FILE), PARTN ULATORY COORDINATOR	22", 10.5#, K55, 9 + 2/10% D-31 + ed rig at 2400