

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Drawer DD

Artesia, NM 88210

SUNDRY NOTICES AND REPORTS RECEIVED

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

JAN 20 1983

2. NAME OF OPERATOR

Yates Petroleum Corporation
ARTESIA OFFICE

3. ADDRESS OF OPERATOR

207 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1790 FSL & 1980 FEL, Sec. 9-6S-26E

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other)

☒

☐

☐

☐

☐

☐

☐

☐

☐

5. LEASE

NM 53957

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

O'Connell VX Federal

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Pecos Slope Abo

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Unit J, Sec. 9-T6S-R26E

12. COUNTY OR PARISH

Chaves

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3614' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS

MINERAL MANAGEMENT SERVICE

ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Started dirt work building location 2:00 PM 11-29-82. Spudded a 14-3/4" hole at 12:00 midnight 12-5-82. Set 40' of 20" conductor pipe. Ran 30 jts of 10-3/4" 40.5# J-55 ST&C casing set at 901'. 1-Texas Pattern notched guide shoe set at 901'. Insert float at 861'. Cemented w/400 sacks Halliburton Lite., 1/4#/sack flocele and 2% CaCl₂. Tailed in w/250 sacks Class "C" 2% CaCl₂. PD 3:45 PM 12-7-82. Bumped plug to 750 psi, released pressure and float held okay. Cement circulated 50 sacks to pit. Drilled out 9:45 PM 12-8-82. WOC 18 hrs. Nippled up and tested to 1000 psi for 30 minutes, okay. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

Production

SIGNED

TITLE Supervisor

DATE

12-10-82

ACCEPTED FOR RECORD

(This space for Federal or State office use)

(ORIG. SGD.) DAVID R. GLASS

APPROVED BY
CONDITIONS

OF APPROVAL IF ANY:

TITLE

DATE

JAN 18 1983

MINERALS MANAGEMENT SERVICE
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side