

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	
OPERATOR	<input checked="" type="checkbox"/>

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

RECEIVED

Form C-103
Revised 10-1-78

FEB 01 1983

O. C. D.

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.

V-134

SUNDRY NOTICES AND REPORTS ON WELLS

ARTESIA, OFFICE

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL
WELL ☐

GAS
WELL ☒

OTHER-

Name of Operator

Yates Petroleum Corporation

Address of Operator

207 South 4th St., Artesia, NM 88210

Location of Well

UNIT LETTER D 660 FEET FROM THE North LINE AND 660 FEET FROM
THE West LINE, SECTION 17 TOWNSHIP 8S RANGE 27E N14PM.

7. Unit Agreement Name

8. Farm or Lease Name

Fox WG State

9. Well No.

1

10. Field and Pool, or Wildcat

Und. Pecos Slope Abo

15. Elevation (Show whether DF, RT, GR, etc.)

4007.5' GR

12. County

Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

TEMPORARILY ABANDON ☐

PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐

CHANGE PLANS ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

COMMENCE DRILLING OPNS. ☐

CASING TEST AND CEMENT JOBS ☐

OTHER Perforate & Treat

ALTERING CASING ☐

PLUG AND ABANDONMENT ☐

☒

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 5600'. WIH and perforated 2366-78' w/8 .42" holes as follows: 2366, 67, 68, 69, 75, 76, 77, and 78'. RIH w/tubing, packer, RBP. Acidized perforations 2366-78' w/1500 g. 15% NE acid and 10 balls. Recovered load and tested well. Show of oil. TOOH. Set cement retainer at 2162' and squeezed perms 2366-78 to 3000# w/150 sacks Class "C" cement. TOOH. Drilled out squeeze cement and tested to 4000#, OK. Drill out DV tool at 2620'. TOOH. TIH w/4-1/2" RTTS. Test DV tool to 4000#, OK. WIH and perforated 4941-5188' w/20 .42" holes as follows: 4941, 42, 43, 5075, 76, 79, 80, 82, 83, 86, 5153, 55, 56, 60, 61, 62, 63, 86, 87, and 88'. RIH w/tubing, packer and RBP. Acidized perforations 4941-5188' w/3000 g. 7½% MOD 101 acid and ball sealers. TOOH w/tools. Sand frac'd perforations 4941-5188' (via casing) w/40000 g. gelled KCL water, 70000# 20/40 sand.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Leslie A. Clements

TITLE Production Supervisor

DATE 1-31-83

Original Signed By

Leslie A. Clements

TITLE Supervisor District II

DATE FEB 02 1983

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY: