

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Drawer DD
Artesia, NM 88210

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to develop a new or different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐ **OIL & GAS**
MINERALS MGMT. SERVICE
ROSWELL, NEW MEXICO
2. NAME OF OPERATOR
Yates Petroleum Corporation
3. ADDRESS OF OPERATOR
207 S. 4th, Artesia, NM 88210
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FNL and 1980' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

- REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:
- | | | |
|----------------------|--------------------------|-------------------------------------|
| TEST WATER SHUT-OFF | <input type="checkbox"/> | <input checked="" type="checkbox"/> |
| FRACTURE TREAT | <input type="checkbox"/> | <input type="checkbox"/> |
| SHOOT OR ACIDIZE | <input type="checkbox"/> | <input type="checkbox"/> |
| REPAIR WELL | <input type="checkbox"/> | <input type="checkbox"/> |
| PULL OR ALTER CASING | <input type="checkbox"/> | <input type="checkbox"/> |
| MULTIPLE COMPLETE | <input type="checkbox"/> | <input type="checkbox"/> |
| CHANGE ZONES | <input type="checkbox"/> | <input type="checkbox"/> |
| ABANDON* | <input type="checkbox"/> | <input type="checkbox"/> |
| (other) | | |

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 14-3/4" hole 8:30 PM 12-17-82. Ran 31 joints of 10-3/4" 40.5# J-55 ST&C casing set 947'. 1-Texas Pattern notched guide shoe set 947'. Insert float at 916'. Cemented with 400 sacks Halliburton Lite, 1/4# flocele and 2% CaCl₂. Tailed in with 250 sacks Class "C" 2% CaCl₂. Compressive strength of cement - 1250 psi in 12 hours. PD 6:30 AM 12-19-82. Bumped plug to 900 psi, released pressure and float held okay. Cement circulated 50 sacks. WOC. Drilled out 12:30 AM 12-20-82. WOC 18 hours. Nipped up and tested to 1000# for 30 minutes, OK. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED _____ TITLE _____ DATE 12-21-82
Production Supervisor
(ORIG. SGD.) DAVID R. GLASS
APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

MINERALS MANAGEMENT SERVICE
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side

5. LEASE #
NM-17031
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
RECEIVED
7. UNIT AGREEMENT NAME
JAN 13 1983
8. FARM OR LEASE NAME
Huckabay "TJ" Federal
9. WELL NO.
3
O. C. D.
ARTESIA, OFFICE
10. FIELD OR WILDCAT NAME
Hudes. Pecos Slope Abo
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Unit G- Sec. 19-T8S-R26E
12. COUNTY OR PARISH
Chaves
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3662.3' GL

