

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR
McClellan Oil Corporation ✓
3. ADDRESS OF OPERATOR
P.O. Drawer 730, Roswell, N.M. 88202
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FNL & 660' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

| | | |
|-------------------------|--------------------------|--------------------------|
| TEST WATER SHUT-OFF | <input type="checkbox"/> | <input type="checkbox"/> |
| FRACTURE TREAT | <input type="checkbox"/> | <input type="checkbox"/> |
| SHOOT OR ACIDIZE | <input type="checkbox"/> | <input type="checkbox"/> |
| REPAIR WELL | <input type="checkbox"/> | <input type="checkbox"/> |
| PULL OR ALTER CASING | <input type="checkbox"/> | <input type="checkbox"/> |
| MULTIPLE COMPLETE | <input type="checkbox"/> | <input type="checkbox"/> |
| CHANGE ZONES | <input type="checkbox"/> | <input type="checkbox"/> |
| ABANDON* | <input type="checkbox"/> | <input type="checkbox"/> |
| (other) Casing & cement | | |

5. LEASE
NM-17218
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME RECEIVED
8. FARM OR LEASE NAME
Paula Federal JAN 13 1983
9. WELL NO.
1 O.C.D.
10. FIELD OR WILDCAT NAME
Wildcat ARTESIA, OFFICE
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 12-T14S-R28E
12. COUNTY OR PARISH
Chaves
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3618' G.L.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1-6-83: Drilled to 2950' with 7-7/8" bit. Ran Gearhart CNL-FDC/DLL. Drilled to 2970'. Ran 75 joints of 4½", 10.5 lb/ft casing to 2970'. Cemented with 750 sx of Class "C" 50/50 Poz with 2% gel, 6# salt, .3% CFR-2. Release rig.

RECEIVED
JAN 11 1983

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED Paul R. Rios TITLE Operations Manager DATE January 10, 1983

ACCEPTED FOR RECORD
(This space for Federal or State office use)

APPROVED BY (ORIG. SGD.) DAVID R. GLASS DATE

CONDITIONS OF APPROVAL JAN 12 1983

MINERALS MANAGEMENT SERVICE
ROSWELL, NEW MEXICO

See Instructions on Reverse Side

Set @ OIL & GAS
MINERALS MGMT. SERVICE
ROSWELL, NEW MEXICO