

# RECEIVED

DEC 23 1982

NM OIL CONS. COMMISSION  
Drawer DD  
Artesia, NM 88210

Form Approved.  
Budget Bureau No. 42-R1424

c/sf

UNITED STATES  
DEPARTMENT OF THE INTERIOR OIL & GAS  
GEOLOGICAL SURVEY MINERALS MGMT. SERVICE  
ROSWELL, NEW MEXICO

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR

McClellan Oil Corporation

3. ADDRESS OF OPERATOR

P.O. Drawer 730, Roswell, NM 88202

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 2310' FSL & 660' FWL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) Casing & Cement

5. LEASE

NM-16069

IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

JAN 18 1983

8. FARM OR LEASE NAME

Coyote Federal

O. C. D.

9. WELL NO.

4-Y

ARTESIA, OFFICE

10. FIELD OR WILDCAT NAME

Undesignated Abo

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 7-T8S-R25E

12. COUNTY OR PARISH

Chaves

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3609' G.L.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

12-21-82: Drilled to 1419'. Ran 1419' of 8-5/8", 24 lb/ft casing. Cemented with 400 sx Halliburton Light with 2% CaCl<sub>2</sub> and 300 sx Class "C" with 2% CaCl<sub>2</sub>. Circulated 85 sx. WOC - 18 hrs. N.U. BOP's and test to 800 psi. Resume drilling with 7-7/8" bit.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED David R. Glass TITLE Operations Manager DATE December 22, 1982

ACCEPTED FOR RECORD

(This space for Federal or State office use)

(ORIG. SGD.) DAVID R. GLASS

APPROVED BY  
CONDITIONS OF APPROVAL

JAN 17 1983

MINERALS MANAGEMENT SERVICE  
ROSWELL, NEW MEXICO

\*See Instructions on Reverse Side