

PLUGGED

JULIAN ARD
ACME #1
1980' FSL & 660' FEL
SECTION 4-T8S-R27E
CHAVES COUNTY, NEW MEXICO
LEASE No.: L-978
API NO.: 30-005-61891
SPUD DATE: 12/13/82

13 3/8" @ 813'
840 sx., CIRC.

T. SAN ANDRES @ 1370'

T. GLORIETTA @ 2575'

HOLE IN TUBING AND CASING @ 2300-2500'
TOC @ +/- 2600'

P/A PROCEDURE

- 1 CUT TUBING OFF AT TOP OF PACKER +/- 6180', P.O.H. W/ TUBING
- 2 SET CIBP @ 6175' AND CAP WITH 35' OF CEMENT.
- 3 LOAD CASING WITH 9.0 LB/GAL MUD 6140'-2600'
- 4 TIE ONTO CASING AND ESTABLISH CIRCULATION AROUND ANNULUS THROUGH HOLE @ 2300-2500'
- 5 PUMP 800 SX OF 50/50 POZMIX "C" CEMENT AND LEAVE CASING AND ANNULUS FILLED WITH CEMENT
- 6 CUT OFF WELL HEAD AND INSTALL DRY HOLE MARKER
- 7 CLEAN LOCATION, RIP AND RESEED LOCATION

T. ABO @ 4758'

T. CISCO @ 6016'

T. SILURIAN @ 6398'

T. MONTOYA @ 6590'

T. GRANITE WASH @ 6813'

CIBP @ 6175', W/ 35' OF CEMENT

5 1/2" ARROW C-5 PACKER @ 6200' W/ 10-11,000# TENSION

ATOKA 6268-75', 3000 GALS. ACID (TESTED 141 MCFGD)

CIBP @ 6360'

SILURIAN 6394-6400, 6424-34', 1000 GALS. ACID (TESTED 2 MCFGD + WATER)

CIBP @ 6590'

MONTOYA 6646-54, 500 GALS ACID (TESTED 487 MCFG + 400 BWPD)

5 1/2" @ 6883'
1425 SX.