


OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.I.D.S.	
LAND OFFICE	
OPERATOR	



3a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT DEPTH. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.

7. Unit Agreement Name	
8. Farm or Lease Name John Cannon et al	
9. Well No. 1-Y	
10. Field and Pool, or Wildcat Wildcat - Abo	
11. Location of Well UNIT LETTER <u>W</u> <u>660</u> FEET FROM THE <u>South</u> LINE AND <u>1650</u> FEET FROM THE <u>West</u> LINE, SECTION <u>27</u> TOWNSHIP <u>10S</u> RANGE <u>25E</u> NMPM.	
12. County Chaves	
13. Elevation (Show whether DF, RT, GR, etc.) 3481 GL	

6. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPS. <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spud 12-26-82. - Drill 360' of 17 1/2" hole. Set 350' of 13 3/8 casing. Cemented w/380 sxs. B.J. Lite. Cement circulated to surface.

12-29-82 - Drilled 12 1/4" hole to 715'. Set 708' of 8 5/8" 24# casing. Cemented w/350 sxs. B.J. Lite. Cement did not circulate. Ran temp. survey Top of cement @ 500'. Ran 1" to 437'. Set 20 sxs. plug. Tagged cement @ 396'. Pumped 130 sxs. B.J. Lite. Cement circulated. Nippled up and checked casing and B.O.P. - OK

Drilled 7 7/8" hole to 4386. Ran 4315 of 4 1/2" 9.5#. Cemented w/350 sxs. 50/50 poz mix.

Released rig 1-12-83.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Clay McElhattan TITLE Exploration Manager DATE Jan. 15, 1983

DATE