

982-1935

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator T.H. McElvain Oil & Gas.			Lease Corn Ranch St. Ut.		Well # 1
Location of Well	Unit J	Section 29	Township 8	Range 22	County CHAVES
Drilling Contractor	Young		Type of Equipment ROTARY		

* WITNESS

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
12 1/4"	8 5/8"	24#	NEW	900'	circ.
7 7/8"	4 1/2"	10.5#	"	3800'	450

Casing Data:

Surface _____ joints of _____ inch _____ # Grade _____
(Approved) (Rejected)

Inspected by _____ date _____

Cementing Program

Size of hole 12 1/4" Size of Casing 8 5/8" Sacks cement required _____

Type of Shoe used Tex. Pt. Float collar used inst. Btm 3 jts welded up

TD of hole 804 Set 800 Feet of 8 5/8" Inch 24 # Grade J-55

New-used csg. @ 800 with 300 sacks neat cement around shoe C.I.C. 2% CaCl₂
+ 150 sax PACSETER LITE additives 1/4 celeceal + 2% CaCl₂

Plug down @ 11:20 (AM) (PM) Date 7-22-83

Cement circulated NO No. of Sacks _____

Cemented by WESTERN Witnessed by LARRY BROOKS

Temp. Survey ran @ 7:30 (AM) (PM) Date 7/23/83 top cement @ 480'

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: TAGGED AT 474' PUMPED 50 SKS. C.I.C. 4% CaCl₂ TAGGED AT

474', PULLED 1" DRY, REDIMIXED W/ 7 1/2 yards.