

(November 1962)  
(Formerly 9-331)

UNITED STATES DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
NM Oil Conservation Division  
Artesia, NM 88210

Expires April 1, 1985  
5. LEASE DESIGNATION AND SERIAL  
77M-32331  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

McKay Oil Corporation

3. ADDRESS OF OPERATOR

P.O. Box 2014, Roswell, NM 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below)  
At surface

1980/syW

Wt. H

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GK, etc.)

4522' GL

JUL 17 '89

O. C. D.

ARTESIA, OFFICE

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Lewis Ranch Federal

9. WELL NO.

#1

10. FIELD AND POOL OR WILDCAT

Wildcat

11. SEC., T., R., M., OR B.L. AND SURVEY OR AREA

Sec. 34-4S-21E

12. COUNTY OR PARISH 13. STATE

Chaves

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

Plug & Abandon

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Operator plans to plug and abandon well as follows:

1. Set CIBP at 2860'.
2. Set 5 sxs cement plug & 2860' to 2800' to cap CIBP.
3. Set 25 sxs cement plug & 1450' - 1135' to cover Glorietta and 7 5/8" casing shoe.
4. Set 5 sxs cement plug & 60' - surface.
5. Displace casing with mud between cement plugs.
6. Set dry hole marker.
7. Rehabilitate surface of location and road as directed by BLM.

Formation Tops

Abo - 2754'

Glorietta - 1392'

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Operations Supervisor

DATE May 9, 1989

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED  
PETER W. CHESTER

MAY 18 1989

\*See Instructions on Reverse Side

BUREAU OF LAND MANAGEMENT  
ROSWELL RESOURCE AREA

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.