

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐

2. NAME OF OPERATOR  
Mesa Petroleum Co.

3. ADDRESS OF OPERATOR  
P.O. Box 2009 / Amarillo, TX 79189

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FNL & 1650' FEL

AT TOP PROD. INTERVAL: same

AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) TD, 4 1/2" casing & cement

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled 7 7/8" hole to TD of 3200' on 6-18-83. Ran 83 jts of 4 1/2", 10.5#, K55, ST&C Casing set at 3199'. Cemented with 450 sx "C" + 10% Gypseal + 2% CaCl and tailed in with 200 sx "C" + 2% CaCl. PD at 0030 6-19-83. Cement did not circulate. Released rig at 0600 6-19-83. WOCU.

XC: BLM-R (O+6), CEN RCDS, ACCTG, MAT CONT, OPS(FILE), MIDLAND, ROSWELL, PARTNER:

Subsurface Safety Valve: Manu. and Type

Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

Regulatory

SIGNED

*R. E. Martin*

TITLE

Coordinator

DATE

June 20, 1983

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY.

ACCEPTED FOR RECORD

SEP 6 1983

\*See Instructions on Reverse Side