STATE OF NEW MEXICO	· -		
ENERGY AND MINERALS DEPARTMEN			
NO. OF COMITS RECEIVED	OIL CONSERVAT	TION DIVISION	
DISTRIBUTION	P. O. BOX	2088 RECEIVED	Form C-103
SANTA FE	SANTA FE, NEW	MEXICO 87501	Revised 10-1-78
FILE	• • • • • • • • • • • • • • • • • • • •	-	5a. Indicate Type of Lease
U.S.G.S.		FEB 23 1983	
LAND OFFICE			
OPERATOR		O. C. D.	5. State Oil & Gas Lease No. LG-4333
SUNDRY 100 NOT USE THIS FORM FOR PROPO USE "APPLICATIO	NOTICES AND REPORTS ON V DEALS TO DRILL OR TO DEEPEN OR PLUG BAL H FOR PERMIT	ARTESIA, OFFICE VELLS CK TO A DIFFERENT RESERVOIR. PROPOSALS.	
· · · · · · · · · · · · · · · · · · ·		· · · · · · · · · · · · · · · · · · ·	7. Unit Agreement Name
	OTHER-		
2. Name of Operator	8. Farm or Lease Name		
Yates Petroleum Corp	Skinny QO State		
2. Address of Operator			9. Well No.
207 South 4th St., A	6		
4. Location of Well			10. Field and Pool, or Wildcat
UNIT LETTER	Pecos Slope Abo		
UNIT CLITCH	, FEI FROM TRE		
West	16 6S	25E	
THELINE, SECTION	TOWNSHIP	PANGE	^{имрм.} ())))))))))))))))))))))))))))))))))))
TITITITITITITITITITI	15. Elevation (Show whether D	F RT GR etc.	12. County
	3995' GR		Chaves
16. Check A	ppropriate Box To Indicate Na	ture of Notice. Report o	r Other Data
NOTICE OF INT		•	JENT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING
TEMPORATILY ABANDON		COMMENCE DRILLING OPHS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING	CHANGE PLANS	CASING TEST AND CEMENT JOB	۲ <u> </u>
		OTHER	́ П
OTHER			
	rutions (crearry state arr pertinent detai	is, and give pertinent adles, inc.	luding estimated date of starting any proposed

work) SEE RULE 1103.

Spudded a 14-3/4" hole at 12:00 noon 2-13-83. Set 40' of 20" conductor pipe. Ran 27 joints of 10-3/4" 40.5# J-55 ST&C casing set at 925'. 1-Type "M" notched guide shoe set at 925'. Flapper insert float set at 892'. Cemented w/400 sacks Halliburton Lite, 1/4#/ sack flocele, 3% CaCl₂. Tailed in with 250 sacks Class "C" 2% CaCl₂. Compressive strength of cement - 1250 psi in 12 hours. PD 11:30 PM 2-14-83. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 50 sacks. WOC. Drilled out 5:30 AM 2-15-83. WOC 18 hours. Cut off and welded on flow nipple. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

	mh. William	*	OIL AND GAS INSPECTOR	FEB 2 5 1983
NED	inter Dordlett	TITLE	Production Supervisor	DATE 2-17-83
. I hereby c	vertify that the information above is true and complet \widehat{C}_{i}	e to the b	est of my knowledge and belief.	

ONDITIONS D	FAP	PROV	AL,	١F	ANY
-------------	-----	------	-----	----	-----