

C/S 74

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐  
well well

2. NAME OF OPERATOR

DEPCO, Inc. ✓

3. ADDRESS OF OPERATOR

803 Central, Odessa, TX 79761

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: S-1980 FSL & 1680 FWL, Sec. 20

AT TOP PROD. INTERVAL:

T-5-S, R-15-E

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) ☐

5. LEASE

36408

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME RECEIVED

8. FARM OR LEASE NAME

Rose Federal

MAY 02 1983

9. WELL NO.

8

O. C. D.

10. FIELD OR WILDCAT NAME

Pecos Slopes Abo

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 20, S. 25

12. COUNTY OR PARISH

Chaves

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3821 GR

APR 26 1983

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

4-20-83: Drilled out to 4161' FSTO. Perf w/1 - .44" hole & 3696-3700', 3739', 40', 3796-3806', 11-13', 20-26', 59-64'.

4-21-83: Acidized perforations from 3659-64' w/900 gals. 7 1/2% HCl acid w/1000 SCF-H<sub>2</sub> p/bbl. Acidized perforations from 3796-3826' w/3300 gals. 7 1/2% HCl acid w/1000 SCF-H<sub>2</sub> p/bbl. Acidized perforations from 3696-3740' w/1200 gals. 7 1/2% HCl acid w/1000 SCF-H<sub>2</sub> p/bbl.

4-22-83: Frac w/59,026 gals. Mini-Max III-30 & CO<sub>2</sub>, 46,400# 10/20 sand & 83,200# 20/40 sand. Preparing to start testing.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED R. L. Denny TITLE Chief Prod. Clerk

DATE 4-25-83

ACCEPTED FOR RECORD

APPROVED BY (ORIG. SGD.) DAVID R. GLASS TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL IF ANY

APR 26 1983

ROSWELL, NEW MEXICO

\*See Instructions on Reverse Side

## Instructions

**General:** This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

**Item 4:** If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

**Item 17:** Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.