

45F

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Artesia, NM 88210

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well ☐ gas ☐ well ☐ other ☐ PLUGGED WELL

2. NAME OF OPERATOR

DWIGHT A. TIPTON

3. ADDRESS OF OPERATOR

P.O. BOX 1597, LOVINGTON, NEW MEXICO 88260

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FSL & 1855' FEL OF SEC.29

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☒

(other)

SUBSEQUENT REPORT OF:

RECEIVED

JAN 11 1983

O. C. D.

ARTESIA, OFFICE

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TOTAL DEPTH - 990 FEET. 8-5/8" SURFACE CASING SET AT 313 FEET.

NO COMMERCIAL SHOWS OF OIL OR GAS ENCOUNTERED.. PROPOSE TO PLUG AND ABANDON BY SETTING CEMENT PLUGS AS FOLLOWS:

100-SACK CEMENT PLUG IN INTERVAL 610-990 FEET

100-SACK CEMENT PLUG IN INTERVAL SURFACE-369 FEET

THIS CONFIRMS ORAL APPROVAL GIVEN 7-10-82.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Arthur Brown TITLE Agent

DATE December 27, 1982


APPROVED BY (ORIG. SGD.) DAVID R. GLASS

CONDITIONS OF APPROVAL, IF ANY:

JAN 10 1983

JAMES A. GILLHAM
DISTRICT SUPERVISOR

*See Instructions on Reverse Side



JAN 4 1983

MINERALS
ROSWELL, NM