

# NM OIL CONS. COMMISSION

Drawer DD

Artesia, NM 88210

Form Approved.

Budget Bureau No. 42-R1424

Form 9-331

RECEIVED BY

MAY 07 1985

O. C. D.  
ARTESIA OFFICE

UNITED STATES

DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☐ other ☒ PLUGGED WELL

2. NAME OF OPERATOR

DWIGHT A. TIPTON

3. ADDRESS OF OPERATOR

P.O. BOX 1597, LOVINGTON, NEW MEXICO 88260

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FSL & 1855' FEL OF SEC.29

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other)

SUBSEQUENT REPORT OF:

☐

☐

☐

☐

☐

☐

☐

XXXX

5. LEASE

NM-16094

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

HAGERMAN 29 FEDERAL

9. WELL NO.

2

10. FIELD OR WILDCAT NAME

WILDCAT - San Andres

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

SEC.29, T.14 S., R.27 E.

12. COUNTY OR PARISH

CHAVES

13. STATE

NEW MEXICO

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3434.6 GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

WELL PLUGGED AND ABANDONED 7-10-82 BY SETTING CEMENT PLUGS AS FOLLOWS:

RAN TUBING TO BOTTOM, SPOTTED 100-SACK, CLASS "C" CEMENT PLUG. TAGGED TOP OF PLUG AT 630 FEET. THIS PLUG IS IN THE INTERVAL 630- 990 FEET.

RAN TUBING TO 369 FEET. SPOTTED 100-SACK CEMENT PLUG. CEMENT CIRCULATED TO SURFACE. THIS PLUG IS IN THE INTERVAL SURFACE TO 369 FEET. DRILLING FLUID BETWEEN PLUGS.

LOCATION IS CLEANED UP.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Arthur R. Brown

TITLE

Agent

DATE

December 27, 1982

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

PETER W. CHESTER

MAY 3 1985

RECEIVED

MAY 4 1985

c/5F

Post ID-2  
2-25-83  
y+A