				C/8 7
Form 9-331 NN OIL Dec. 1973 Drawon	CONS. COMMI	SSION	Form Approved. Budget Bureau No	·
UNITED STATES Drawer Artesia DEPARTMENT OF THE INTERIOR		5. LEASE		
GEOLOGICAL SURVEY		MM-38476 6. IF INDIAN, ALLOTTEE OR TRIBE NAM RECEIVED		
SUNDRY NOTICES AND REPORTS OF (Do not use this form for proposals to drill or to deepen or plug to reservoir, Use Form 9–331–C for such proposals.)		 UNIT AGREEME 8. FARM OR LEAS 		MAR 1 9 1983
1. oil gas de other well	- · ·	Salt Grass "W 9. WELL NO.	S" Federal	O. C. D. ARTESIA, OFFICE
2. NAME OF OPERATOR				· · · · ·
Yates Petroleum Corporation		10. FIELD OR WILDCAT NAME Wildcat Burnsto Unley James		
 207 S. 4th St., Artesia, NM 88210 4. LOCATION OF WELL (REPORT LOCATION CLEARLY below.) 	. See space 17	11. SEC., T., R., M. AREA Sec. 26-T14S-	, OR BLK. AND S	
AT SURFACE: 1980' FSL & 660' FEL AT TOP PROD. INTERVAL: AT TOTAL DEPTH:		12. COUNTY OR PA Chaves 14. API NO.	NRISH 13. STAT	re
16. CHECK APPROPRIATE BOX TO INDICATE NATUR REPORT, OR OTHER DATA	E OF NOTICE,	15. ELEVATIONS (SHOW DF, KDB	, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT F TEST WATER SHUT-OFF	REPORT OF:	CIL	orm 9-330.) 10 1983) & 638	De or zone
(other)	NO (0)	MINERALS I	MGMT. SERVICE	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, "Shu give Gertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 17-1/2" hole 10:15 am 3-5-83. Ran 7 joints of 13-3/8" 48# J-55 ST&C casing set 300'. 1-Texas Pattern notched guide shoe set 300'. Insert float set 257'. Cemented with 325 sacks Class "C" 2% CaCl₂. Compressive strength of cement - 1250 psi in 12 hours. PD 12:45 am 3-6-83. Bumped plug to 750 psi, released pressure and float held okay. Cement did not circulate. WOC 6 hours. Ran Temperature Survey and found top of cement - 35'. Spotted 4 yards of pea gravel. WOC. Drilled out 9:00 pm 3-6-83. WOC 20 hours and 15 minutes. Cut off and welded on flow nipple. Reduced hole to 12-1/4". Drilled plug and resumed drilling. Permission obtained from Minerals Management to use pea gravel.

Subsurface Safety Valve: Manu. and Type	Set @	Ft.
18. I hereby certify that the foregoing is true and correct		
SIGNED (Child - or alla 11 TITLE Production Supervisor DATE	3-9-83	
CCEPTED FOR TECORD (This space for Federal or State office use)		
APPROVED BY (ORIG. SGD.) DAVID R. GLASS	E	
CONDITIONS OF APPROVAL IF ANY: MAR 16 1983		
THNERALS MANAGEMENT SERVICE		
LOSWELL, NEW INSXICO •See Instructions on Reverse Side		