

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980 FSL & 660 FEL, Sec.26-14S-27E
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) Intermediate Casing ☒

SUBSEQUENT REPORT OF:

RECEIVED

MAR 16 1983

GLASS
MINERALS MGMT. SERVICE
POSWELL, NEW MEXICO

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Ran 36 jts of 8-5/8" 24# J-55 casing set 1550'. 1-Texas Pattern notched guide shoe set 1550'. Insert float set 1506'. Cemented w/670 sacks Pacesetter Lite, 3% CaCl₂. Tailed in w/300 sacks Class "C" 2% CaCl₂. Compressive strength of cement - 1250 psi in 12 hrs. PD 5:15 PM 3-8-83. Bumped plug to 1000 psi, released pressure and float held okay. Cement did not circulate. WOC 6 hrs. Ran Temperature Survey and found top of cement at 425'. Ran 1". Tagged cement 500'. Spotted 600 sacks Class "C" 3% CaCl₂. PD 3:30 AM 3-9-83. WOC 3 hrs. Ran 1". Tagged cement 416'. Spotted 350 sacks Class "C" 3% CaCl₂. PD 7:15 AM 3-9-83. Cement circulated 5 sacks. WOC. Drilled out 6:30 PM 3-9-83. WOC 25 hrs and 15 minutes. NU and tested to 1000 psi for 30 minutes, okay. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

Subsurface Safety Valve: Manu. and Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED DAVID R. GLASS TITLE Production Supervisor DATE 3-15-83

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL

(ORIG. SGD.) DAVID R. GLASS

MAR 16 1983

MINERALS MANAGEMENT SERVICE
POSWELL, NEW MEXICO

*See Instructions on Reverse Side

5. LEASE

NM 38476

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Salt Grass WS Federal

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Wildcat Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Unit I, Sec. 26-T14S-R27E

12. COUNTY OR PARISH

Chaves

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3444' GR

RECEIVED

MAR 19 1983

O. C. D.
ARTESIA, OFFICE