

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

RECEIVED

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	☒
FILE	☒
U.S.G.S.	
LAND OFFICE	
OPERATOR	☒

MAR 31 1983

O. C. D.

ARTESIA, OFFICE

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - 1" (FORM C-101) FOR SUCH PROPOSALS.)

5a. Indicate Type of Lease State ☐ Fee ☒
5. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Farm or Lease Name Spool "SU" Com
9. Well No. 4
10. Field and Pool, or Wildcat Under Pecos Slope Abo
12. County Chaves

OIL WELL ☐ GAS WELL ☒ OTHER ☐
Name of Operator Yates Petroleum Corporation
Address of Operator 207 S. 4th St., Artesia, NM 88210
Location of Well UNIT LETTER K 1990 FEET FROM THE South LINE AND 1980 FEET FROM THE West LINE, SECTION 22 TOWNSHIP 7S RANGE 25E N.M.P.M.
15. Elevation (Show whether DF, RT, GR, etc.) 3682.4' GL

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PLATFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPS. ☒	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☒	

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Studied 14-3/4" hole 4:30 pm 3-26-83. Ran 13 joints of 10-3/4" 40.5# J-55 casing set 509'. 1-Texas Pattern notched guide shoe set 509'. Insert float set 465'. Cemented with 200 sacks Thixolite, 1/2#/sx Permacheck, 1/2#/sack celloseal, 400 sacks Pacesetter Lite, 3% CaCl₂. Tailed in with 300 sacks Class "C" 2% CaCl₂. Compressive strength of cement - 1250 psi in 12 hours. PD 2:00 am 3-28-83. Bumped plug to 1000 psi, released pressure and float held okay. Cement did not circulate. WOC 6 hours. Ran Temperature Survey and found top of cement 310'. Ran 1". Tagged cement 310'. Spotted 100 sack Class "C" 3% CaCl₂. PD 10:10 am 3-28-83. WOC 2 hours. Ran 1". Tagged cement 180'. Spotted 100 sacks Class "C" 3% CaCl₂. PD 12:30 pm 3-28-83. WOC 3 hours. Ran 1". Tagged cement at 256'. Spotted 100 sacks Class "C" 3% CaCl₂. PD 3:50 pm 3-28-83. WOC 2 hours. Ran 1". Tagged cement 152'. Spotted 200 sacks Class "C" 3% CaCl₂. PD 6:00 pm 3-28-83. Cement circulated 10 sacks to pit. WOC. Drilled out 2:00 am 3-29-83. WOC 24 hours. Nippled up and tested to 1000# for 30 minutes, OK. Reduced hole to 9-7/8". Drilled plug and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Leslie A. Clements TITLE Production Supervisor DATE 3-30-83
Original Signed By
Leslie A. Clements
APPROVED BY _____ TITLE Supervisor District II DATE APR 04 1983

CONDITIONS OF APPROVAL, IF ANY: