1-File, 1-Engr DW. 1-Foreman 88310 1-JA 1-BW

orm 9–331 Dec. 1973	Budget Bureau No. 42-R1424
UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	NM-54388
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
Do not use this form for proposals (Marill or to deepen a college ack to a different eservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas [V]	Getty GC Federal Com
well well other APR 1 8 1983	9. WELL NO.
2. NAME OF OPERATOR	1
Getty Oil Company G. C. D.	10. FIELD OR WILDCAT NAME
A MINDESS OF OPERATOR	Pecos Slope Abo
P.O. Box 730, Hobbs, New MEXISO 88240	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA
below.)	Sec 7, T-6S, R-26E 12. COUNTY OR PARISH 13. STATE
AT SURFACE: Unit Ltr. C, 660' FNL & 1980' FWL AT TOP PROD. INTERVAL:	Chaves NM
AT TOTAL DEPTH:	14. API NO.
6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	24.711110.
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
(1	3779.5' GR
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	DECENTA
REPAIR WELL	(NOTE Proport results of multiple completion or zone
PULL OR ALTER CASING U	APR 1 1 1983
CHANGE ZONES	W W 7 T 1900
ABANDON*	Commence of the second
(other) Spudded & Drilling (X)	Maranalo karaka bumasa
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state	

Spudded well @ 12:30 PM. Drilling 14 3/4" hole @ 676'. 3/29/83 Ran casing to 806' and stuck, wouldn't go up or down. Ran 18 jts of 11 3/4", 3/30/83 42#, K-55, 793' and set @ 806'. G.S. @ 805' and F.S. @ 763'. Cement by Halliburton w/ 350 sxs light w/ 1/4# / sx flocele and 2% CaCl. Tailed in w/ 200 sxs class "C" w/ 2% CaCl. Circulate 75 sxs. Bumped plug @ 5:00 AM. Ran 94 jts (4187'), 5 1/2 OD, 15 1/2#, K-55 set @ 4200'. FC @ 4161', DV 2021', 4/7/83 10 centralizers 4125-3800'. 1st stage 500 sxs 50-50 poz, 5# salt at 4:15 PM. Open DV tool did not circ. 2nd stage 250 sxs lite, 5# salt, 550 sxs 50-50 poz, 5% salt. Plug down 9:15 PM. Circ 57 sxs. Release rig @ 2:30 AM.

	Subsurface Safety Valve: Manu. and Type Fig. 1.	t.
	C	
	18. I hereby certify that the foregoing is true and correct	
	SIGNED D.R. Crockett Area Superintendent April 8, 1983	
,	D.R. Crockett	_
	ACCEPTED FOR RECORDs space for Federal or State office use)	
	(ORIG. SGD.) DAVID R. GLASS	
	CONDITIONS OF APPROVAPR 45 1983	