

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

IL CONSERVATION DIVISIO..
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

3a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
3. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL OTHER-	7. Unit Agreement Name
2. Name of Operator Sanders Oil & Gas Company	8. Farm or Lease Name Cannon Bitter Lake
3. Address of Operator 14679 Midway Road, Suite 101, Dallas, Texas 75234	9. Well No. 1
4. Location of Well UNIT LETTER <u>I</u> 1980 FEET FROM THE <u>South</u> LINE AND <u>660</u> FEET FROM THE <u>East</u> LINE, SECTION <u>17</u> TOWNSHIP <u>10S</u> RANGE <u>25E</u> N.M.P.M.	10. Field and Pool, or Wildcat Undes. S. Pecos Slope, Abo
15. Elevation (Show whether DF, RT, GR, etc.) 3518.01 GR	12. County Chaves

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

11-23-83 - Move in, rig up rotary rig.

11-24-83 - Spud in - 12 1/4" hole.

11-25-83 - Drilled to 660'. Ran 15 jts. 8 5/8" 24# J-55 casing, set at 653'. Cemented with 245 sx. pace setter lite and 150 sx. Class C w/2% Cacl. Cement did not circulate. Tagged top of cement at 165' w/1" Kobe pipe. Cemented w/130 sx. Class C cement w/3% Cacl. Circulated 15 sx. of cement to pits.

11-26-83 - WOC 18 hrs. Pressure tested casing and BOP at 1200 psi for 30 min. OK

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Wm. Schuttaker TITLE Exploration Manager DATE 12-5-83

APPROVED BY R. [Signature] TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: