Drawer DD

Artesia, Na 88210

Form Approved. Budget Bureau No. 42-R1424

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

| 5. | LEASE |
|----|-----------------------------------|
| | NM 24612 |
| 6. | IF INDIAN, ALLOTTEE OR TRIBE NAME |
| 7. | UNIT AGREEMENT NAME |
| Я | FARM OR LEASE NAME |

Excalibur XC Federal

| SUNDRY | NOTICES | AND | REPORTS | ON | WELLS |
|--|---------|-----|---------|-----------|------------------|
| (Do not use this for reservoir, Use Form | | | | plug baci | k to a different |

1. oil gas other P&A

well well other P&A

2. NAME OF OPERATOR

Yates Petroleum Corporation
3. ADDRESS OF OPERATOR

207 South 4th St., Artesia, NM 88210

LOCATION OF WELL (REPORT LOCATION CLEARLY, See space 17 below.)
 AT SURFACE: 1980 FNI. & 660 FEL. Sec. 13-48-24E

AT SURFACE: 1980 FNL & 660 FEL, Sec.13-4S-24E AT TOP PROD. INTERVAL: AT TOTAL DEPTH:

16. CHECK APPROPEIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

10. FIELD OR WILDCAT NAME Und. Pecos Slope Abo

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Unit H, Sec. 13-T4S-R24E

12. COUNTY OR PARISH 13. STATE Chaves NM

14. API NO.

9. WELL NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD) 3973.4 GR

REQUEST FOR APPROVAL TO:
TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
PULL OR ALTER CASING
MULTIPLE COMPLETE
CHANGE ZONES
ABANDON*
(other)

SUBSEQUENT REPORT OF:

RECEIVED BY
(NOTE: Repo

O. C. D.
ARTESIA, OFFICE

APR 20 1983

PT 9 PEG

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertition)? (Etes, including estimated date of starting any proposed work. If well is directionally drilled, gpus subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plugged well as follows:

Plug #1: 35 sacks Class "C" Neat. Tagged top at 3505'. Set 3625-3525'.

Plug #2: 35 sacks Class "C" Neat. Set 1640-1540'.

Plug #3: 75 sacks Class "C" Neat. Set 1014-914'.

Plug #4: 10 sacks Class "C" Neat. Set surface.

Heavy mud placed between plugs. Dry hole marker will be installed and pits leveled. Location cleaned and restored according to regulations.

Verbal permission for plugging obtained from Mr. George Stewart, U.S. Dept. of Interior, Roswell, NM, 4-14-83.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

Production

SIGNED L. This shace for Federal or State office use)

(OR.G. SGD.) DAVID R. GLASS

APPROVED BY (OR.G. SGD.) DAVID R. GLASS

TITLE DATE

CONDITIONS OF APPROVED BY 1002